

O&M strategies A lifetime optimisation process

7th annual Wind Energy O&M Forum

René van de Pieterman
Hamburg, 20-21 January 2015



ECN at a glance

Mission:

...To develop, with and for the market, knowledge and technologies that enable a transition to more sustainable energy systems.


Founded in **1955**

5 Commercial licensing deals p/y

600 Employees

+/-20 patents a year

€ 80 M annual turnover



Solar energy



Biomass



Policy studies



Energy efficiency



Wind energy



Environment & energy engineering

Innovative solutions to lower the cost of energy



Contents

- Introduction – Offshore O&M
- O&M strategy – Planning Phase
- O&M Optimisation – Operational Phase
- O&M Optimisation – Case study
- Lifetime extension
- Conclusions

Introduction

Typical O&M concepts


- Near shore / smaller farms
 - Workboat for transfer of crew and small spare parts
 - Optional: helicopters for crew transfer
 - Heavy lift vessel for large component replacement
- Far-offshore / larger farms
 - Fixed base / Mother vessel?
 - Reduce travel time
 - Increase accessibility



Example of typical near shore maintenance strategy



Examples of offshore service vessels



Examples of compensated access gangways

O&M strategy – Planning Phase

Planning for successful O&M

Wind Farm Developers

- Find the optimal O&M strategy for a given wind farm
- Quantify O&M costs and risks for project financing
- Selection of vessels and equipment
- Verify O&M quotations from OEM's and discuss starting points


Turbine Manufacturers

- Improve design from reliability and maintainability of design
- Prepare O&M strategy and quotations for clients



Vessel and access system developers

- Quantify the effect of design assumptions
- Establish business case for new innovative solutions

Example



5 offshore wind farms, 5 O&M scenario's



Source background image: 4coffs

O&M Optimisation – Operational Phase

The most important phase!

Predictive maintenance

- Avoid long unexpected downtimes
- Reduce costs by planning ahead and clustering

Make well-founded decisions

- Identify options for increasing production and reducing costs
- New O&M contracts, vessels and equipment
- Solid background for O&M budget
- Assist in planning predictive maintenance



Value of operational data: Example

- Inventory of O&M data for 3 month period of RWE's Rhyl Flats wind farm:
 - List of SCADA parameters
 - Alarm list
 - Meteo and wave data
 - Monthly downtime summary reports
 - Daily work reports
 - Turbine breakdown
 - Daily vessel reports
- Observations
 - Many different data sources stored independently and in different formats
 - ECN used supplied O&M data to manually structure and fill Event List format
 - Sufficient (92%) data available for data analysis

Event nr.		1	
Start event	[date/time]	15/02/2013 09:33	
Event type		Corrective maintenance	
Turbine ID or BOP ID		1. Turbine A	
Nr. maintenance action		1.1	
Start	[date/time]	15/02/2013 09:33	16/02/2013 08:30
End	[date/time]	15/02/2013 14:33	16/02/2013 17:00
Duration	[h]	1.05	8.50
Downtime	[h]	5.00	8.50
Type of maintenance		Inspections	Replacement (finalisation)
Weather downtime	[h]	4.00	0.00
Scada alarm code		0001	0010
Scada description		Temperature error	Turbine stopped by operator
Reported labour hours	[h]	2.00	
Crew size		2	
Access equipment		Access vessel	
- travel time (heading out)	[h]	0.75	
- travel time (return)	[h]	1.00	
- fuel consumption	[dm ³]	200	225
Second equipment		n.a.	n.a.
- travel time (one way)	[h]		
- mobilisation time	[h]		
Third equipment		n.a.	n.a.
- travel time (one way)	[h]		
- mobilisation time	[h]		
Explanations		Pitch motor overheated	Replaced pitch drive blade A
Main system ID		MDC Blade adjustment	
Component ID		GL001 Pitch drive assembly A	
Work carried out		Replacement	
Spare part in stock		Yes	
Logistic time spare part	[h]	2	
Consumables		n.a.	
# consumables			
Total labour hours	[h]	27.50	
End event		16/02/2013 17:00	
Duration event	[h]	31.44	
Downtime event	[h]	31.44	


Start and definition of event

Definition of individual maintenance actions

End of event and reporting



Value of operational data: Key performance information

- Apply dedicated data analysis tools to obtain actual O&M performance:
 - Trends in failure behaviour
 - Insight in repairs
 - Details on spare part usage
 - Operation of vessels and equipment
- Implement and evaluate improvement plans:
 - Is component reliability improving after solving teething issues?
 - Is the same repair performed quicker as more experience is gained?
 - Is my vessel and crew operating up to its designed limits?



Value of operational data: O&M cost modelling

- Reliable prediction O&M effort using O&M Calculator tool:
 - Based on accurate input derived from operational experience
- Well-founded decision making:
 - Identify options for increasing production and reducing costs
 - New O&M contracts, vessels and equipment
 - Solid background for O&M budget
 - Assist in planning predictive maintenance




O&M Optimisation – Case study

Case study Rhyl Flats wind farm



- Step 1: Reference calculation O&M costs
 - Based on historical data and assumptions

Summary of downtime & costs				
Project	Rhyl Flats baseline		Key simulation results (average)	
Installed wind farm capacity	90,0	MW	Availability [time/yield]	94 / 93.2%
Number of wind turbines in farm	25		Costs [c€/kWh]	4,52
Simulation	sim		Repair costs [M€/yr]	12,51
Simulation period	1	yr	Rev. losses [M€/yr]	2,63
Start-up period	1	yr	Total effort [M€/yr]	15,14
Number of simulations	1000			



Case study

- Step 2: Analysis operational data
 - 3 months of operational data
 - Derived estimated failure rates of components



Case study

- Step 3: Update calculation O&M costs
 - Based on updated input data (e.g. failure rates)

Summary of downtime & costs				
Project	Rhyl Flats updated		Key simulation results (average)	
Installed wind farm capacity	90,0	MW	Availability [time/yield]	96.2 / 95.8%
Number of wind turbines in farm	25		Costs [c€/kWh]	3,35
Simulation	sim		Repair costs [M€/yr]	9,52
Simulation period	1	yr	Rev. losses [M€/yr]	1,64
Start-up period	1	yr	Total effort [M€/yr]	11,16
Number of simulations	1000			

- Step 4: Implement O&M strategy improvements
 - Reduce number of available access vessels & technicians
 - Only perform preventive maintenance when wind speeds are below 4 m/s



Summary of downtime & costs				
Project	Rhyl Flats optimised		Key simulation results (average)	
Installed wind farm capacity	90,0	MW	Availability [time/yield]	96.2 / 96%
Number of wind turbines in farm	25		Costs [c€/kWh]	3,00
Simulation	sim		Repair costs [M€/yr]	8,53
Simulation period	1	yr	Rev. losses [M€/yr]	1,57
Start-up period	1	yr	Total effort [M€/yr]	10,10
Number of simulations	1000			

10% costs reduction
4% revenue increase

Lifetime extension

Lifetime extension

- Offshore wind farms are designed for a 20 year lifetime
- Load case calculations play an important role in the design
- Sizeable safety factors are considered for structural components
- How long can we continue?



Approaching design lifetime...

Keep track of O&M performance

- Consider service history
- Evaluate trends in failure behaviour
- Decide on remaining economic lifetime


Evaluate wind farm load history

- Relative comparison between turbines
- Comparison actual loads with design loads (when available)
- Can be done based on a short-term measurement campaign!

Wind Farm Load History

What measurements are required for a successful assessment?

- Mechanical load measurements
 - Blades and support structure
 - Campaign with one year minimum duration
 - On at least one turbine; preferably two
- SCADA data
 - Standard signals (e.g. power, speed, pitch, etc.)
 - 10-min statistics sufficient; 1 Hz even better
 - For the complete wind farm lifetime!
 - From all turbines!



Conclusions

Summary

- O&M optimisation is important during every phase of the lifetime
- Initial strategy set-up at planning phase using cost modelling tools
- Data analysis and cost modelling should be performed during the operational phase and will lead to reduce costs
- Operational history supported by load measurements and inspections will be required to evaluate remaining economic lifetime

Thank you very much
for your attention

René van de Pieterman
Researcher Wind Energy
vandepieterman@ecm.nl
+31 88 515 4616

