

Period: 12 October 2023 to 5 December 2023

Verification of the Wind@Sea LiDAR system ZX563 at the EWTW test site near meteorological mast MM6

TNO 2024 R10316 – March 2024

Verification of the Wind@Sea LiDAR system ZX563 at the EWTW test site near meteorological mast MM6

Period: 12 October 2023 to 5 December 2023

Author(s)	C. Liu and G. Bergman
Classification report	TNO Public
Number of pages	62 (excl. front and back cover)
Number of appendices	2
Sponsor	Ministry of Economic Affairs and Climate (EZK)
Project name	MinvEZ 2023 Windconditions@northea
Project number	060.55419

All rights reserved

No part of this publication may be reproduced and/or published by print, photoprint, microfilm or any other means without the previous written consent of TNO.

©2024 TNO

Revision

Rev.	Date	Description	Page	†
1.0	01 Mar 2024	First release		

†: (a) customer request, (b) correction, (c) addition

Archiving

<https://365tno.sharepoint.com/teams/P060.55419/>

		 
TNO Wind Energy is accredited conform ISO / IEC 17025 and accepted as RETL under IECRE WE. › Power performance measurements conform to IEC 61400-12-1, MEASNET Power Performance measurement procedure, FGW TR2, FGW TR5 › NTF/NPC measurements conform to IEC 61400-12-2 › Mechanical loads measurements conform to IEC 61400-13 › Meteorological measurements (wind speed, wind direction, temperature, air pressure and relative humidity) conform to IEC 61400-12-1 › Verification of ground-based or nacelle-mounted Remote Sensing Devices conform to IEC 61400-12-1, Appendix L › Verification of Floating LiDAR Systems conform to IEC 61400-12-1, Appendix L and IEA Recommended Practices 18		

Adaptation of scope for remote sensing verification to IEC 61400-50-2 by RvA is currently pending.

Results only apply for the tested LiDAR with the settings used during the measurement period. In case copies of this report are made, only integral copying is allowed.

Contents

Contents	4
List of tables and figures	5
Abbreviations	6
Management summary	7
1 Introduction.....	8
2 Measurement campaign.....	9
2.1 RSD verification location	9
2.2 Measurement sector	11
2.3 Remote Sensing Device	12
2.4 Data stream	13
3 Data selection.....	15
3.1 Filter criteria	15
4 LiDAR verification	18
4.1 Direct data comparison	18
4.2 Bin-wise data comparison	18
4.3 Systematic uncertainties	18
4.4 Environmental conditions	19
5 Sensitivities	28
5.1 Sensitivity analysis.....	28
5.2 Impact on accuracy	29
6 Uncertainty	34
6.1 Reference devices - cup anemometers	34
6.2 Remote sensing device	35
7 Deviations	36
8 Conclusions.....	37
References.....	38
Signature	39
Appendices	
Appendix A: IEC visualisations	40
Appendix B: Instrumentation details	42

List of tables and figures

Tables

2.1	Coordinates of the reference mast as well as the LiDAR.....	11
2.2	Excluded sectors per measuring height.	12
2.3	Measurement heights for verification	13
4.1	LiDAR verification IEC 61400-50-2 results.....	18
4.2	Uncertainty calculations of the LiDAR @117.5 m	22
4.3	Uncertainty calculations of the LiDAR @81.4 m.....	23
4.4	Uncertainty calculations of the LiDAR @41.9 m.....	24
4.5	Environmental conditions @117.5 m.....	25
4.6	Environmental conditions @81.4 m.....	26
4.7	Environmental conditions @41.9 m.....	27
5.1	Overview of significant sensitivities	30
5.2	Sensitivity to environmental variables for the LiDAR	31
5.3	Maximum influence of environmental variables on the LiDAR wind speed	32
5.4	Distribution of environmental variables used in the LiDAR sensitivity study	33
B.1	Signals used for each comparison height	42
B.2	List of measured signals.....	43
B.3	List of equipment used per signal.....	44
B.4	List of calculated (pseudo) signals	45

Figures

2.1	Detailed overview of the south EWTW locations.....	9
2.2	Ground level elevation map of the LiDAR's surroundings	10
2.3	Meteorological Mast MM6.....	10
2.4	Position of the LiDAR relative to meteorological mast	11
2.5	Layout of the EWTW test site used to determine the measurement sector	12
2.6	ZX 300M ZX563 at the RSD verification location.....	13
2.7	Layout of the meteorological mast MM6	14
3.1	Unfiltered wind speed time series	15
3.2	Unfiltered wind direction time series.....	16
3.3	Filter: MEASNET icing criterion.....	17
4.1	Wind speed comparison @117.5 m	20
4.2	Wind speed comparison @81.4 m	20
4.3	Wind speed comparison @41.9 m	20
4.4	Bin-wise wind speed comparison @117.5 m	21
4.5	Bin-wise wind speed comparison @81.4 m.....	21
4.6	Bin-wise wind speed comparison @41.9 m.....	21
A.1	Influence of the wake of meteorological mast on the LiDAR.....	40
A.2	Contributions to the LiDAR uncertainty	41
A.3	Histograms for bin-wise wind speed comparison	41

Abbreviations

α	exponent of the power law wind shear model, see equation (5.2)
AHN	Actueel Hoogtebestand Nederland (Dutch laser altimetry map)
DTM	Digital Terrain Model
EV	environmental variable
EWTW	ECN Wind Turbine test site Wieringermeer
h	measurement height, see equation (5.2)
h_r	reference height for shear profile, see equation (5.2)
IEC	International Electrotechnical Commission
IECRE WE	IEC system for certification to standards relating to equipment for use in Renewable Energy applications - Wind Energy
ILAC MRA	International Laboratory Accreditation Cooperation Mutual Recognition Arrangement
N	number of 10-minute samples, see equation (5.6)
n_b	number of bins, see equation (5.6)
n_i	bin-count for bin i , see equation (5.6)
PDOK	Publieke Dienstvoorziening Op de Kaart
RD	Rijksdriehoekscoördinaten (Dutch geodetic datum)
RETL	Renewable Energy Testing Laboratory
RSD	Remote Sensing Device
RvA	Raad voor Accreditatie (Dutch Accreditation Council)
std	standard deviation
TNO	Nederlandse Organisatie voor toegepast-natuurwetenschappelijk onderzoek (Netherlands Organisation for applied scientific research)
UTC	Coordinated Universal Time
v_{hor}	horizontal wind speed, see equation (5.4)
v_r	wind speed of shear profile at h_r , see equation (5.2)
v_{vert}	vertical wind speed, see equation (5.4)
v_d	wind direction, see equation (5.5)
WDMS	Wind Data Management System
WGS 84	world geodetic system 1984

Management summary

As part of the Wind@Sea project a ZX Lidars ZX 300M with serial number ZX563 was installed at the EWTW test site near meteorological mast MM6 on 12 October 2023. The LiDAR was validated before using it for wind field measurements at Lichteiland Goeree.

The official measurement campaign started on 12 October 2023 12:20 UTC and lasted until 5 December 2023 00:00 UTC, covering 53 days. The comparison of the LiDAR against meteorological mast MM6 is performed for 3 measurement heights, 42 m, 81 m and 118 m.

For all comparison heights the regression slope is close to 1.00 and the offset is up to 0.05 m/s with an R^2 close to 1. The maximum deviation observed is 2.1 %. The sensitivity analysis did not result in any significant sensitivities for the LiDAR.

The results of this verification are based on IEC 61400-50-2:2022 (formerly Annex L of the IEC 61400-12-1:2017) standard and the TNO *Work instructions for verification RSD* (v.3).

TNO Wind Energy is ISO 17025 accredited for ground based remote sensing device verification.

1 Introduction

A ZX Lidars ZX 300M with serial number ZX563 was installed at the EWTW test site near MM6 on 12 October 2023. The LiDAR was verified before using it for wind field measurements at Lichteiland Goeree (LEG) in the Wind@Sea project. This report presents the verification results.


After verifying correct operation of the LiDAR, the measurement campaign was started on 12 October 2023 12:20 UTC and lasted until 5 December 2023 00:00 UTC.

The results of this verification are based on the IEC 61400-50-2:2022 [1] (formerly Annex L of the IEC 61400-12-1:2017) standard and the TNO *Work instructions for verification RSD* (v.3).

2 Measurement campaign

2.1 RSD verification location

The LiDAR system is verified near meteorological mast MM6 at the EWTW test site [2]. The terrain at the EWTW test site consists mainly of agricultural land, with single farmhouses and rows of trees as shown in fig. 2.1. It is located in the Wieringermeer, a polder in the north east of the province of North Holland, 3 km North of the village Medemblik and 1 km West from the vast IJsselmeer lake. The altitude is 5 m below sea level. The site is considered sufficiently flat according to IEC 61400-12-5:2022 [3] as demonstrated by the laser altimetry in fig. 2.2.




Source: Google Earth

Figure 2.1: Detailed overview of the south EWTW locations and corresponding meteo mast locations as well as the nearby obstacles. Meteorological mast MM6 is highlighted by the green circle

The mast is an un-guyed triangular lattice tower with a height of 115.5 m, see fig. 2.3. At the bottom the width of the tower is 5.86 m. On the top of the mast a vertical tube is installed with a total height of 1.775 m above the mast top. Including the sensor height of 0.225 m this adds up to a top cup measuring height of 117.5 m.

A total of eight booms are mounted on to the mast, as is presented in the layout drawing in fig. 2.7. Five booms, pointing at 320° in relative to North, support three wind vanes and two cup anemometers. Three booms, pointing at 140° relative to North, support anemometers. At the lower and mid measuring heights two cups are installed in opposite directions. Within the large measurement sector a single cup measurement would result in large wake effects at specific wind direction. Combined, the influence is reduced. At the lower and mid measuring heights the vanes are installed on a separate boom 4 m below the cup measuring height. The



Source: PDOK / AHN-3 (0.5 m raster DTM)

Figure 2.2: Ground level elevation map of the LiDAR's surroundings (radius = 5×117.5 m)



Figure 2.3: Meteorological Mast MM6

measuring heights of the cup anemometers are 41.9 m, 81.4 m, 112.5 m and 117.5 m. The measuring heights of the wind vanes are 37.9 m, 77.4 m and 112.5 m. At 108.5 m, 4 m below the cup anemometer, a sonic anemometer is located. The booms can be retracted for maintenance of the sensors.

In table 2.1 the coordinates of the meteorological mast and LiDAR locations are summarized.

Table 2.1: Coordinates of the reference mast as well as the LiDAR

location	RD	WGS 84
MM6	132 384 m, 536 649 m	52°48.997'N, 5°3.105'E
LiDAR	132 344 m, 536 622 m	52°48.982'N, 5°3.069'E

RD Rijksdriehoeksmeting (Dutch geodetic datum)

WGS 84 world geodetic system 1984

In fig. 2.4 the location of the verification platform is shown in more detail.



Source: Google Maps

Figure 2.4: Position of the LiDAR at 49 m from the meteorological mast; indicated in green is the meteorological mast and in yellow the verification platform

2.2 Measurement sector

The measurement sector is the wind direction sector for which the meteorological mast measurements and LiDAR measurements are unaffected by obstacles. The measurement sector for this verification test is determined based on IEC 61400-12-5:2022 [3] using MeasSector version 2.2.1. In fig. 2.5 the lay-out of the EWTW test site is given with the excluded sectors of all the relevant obstacles. This information is used to determine the undisturbed measurement sector.




Figure 2.5: Layout of the EWTW test site used to determine the measurement sector

The measurement sector is height dependent as for the boom mounted measuring heights an extra sector is excluded where the wind direction is in line with the boom orientation, $320^\circ \pm 10^\circ$, see table 2.2.

Table 2.2: Excluded sectors per measuring height.

Excluded sector	comparison height		
	117.5m	81.4m	41.9m
0.1° to 104.0°	x	x	x
119.4° to 191.2°	x	x	x
310° to 330°		x	x

2.3 Remote Sensing Device

The Remote Sensing Device (RSD) is a ZX 300M LiDAR. This unit has identification number ZX563 (software version 3.3002). It is configured to perform measurements at 10 heights: 21 m, 42 m, 61 m, 81 m, 101 m, 113 m, 118 m, 141 m, 161 m and 181 m. The LiDAR has a cone half-angle of 30° . The comparison heights are specified in table 2.3. During the verification test the LiDAR was oriented 5° w.r.t. North.

The ZX 300M LiDAR at the RSD verification location is presented in fig. 2.6.

Table 2.3: Measurement heights for verification

comparison height	MM6 height	LiDAR height
m	m	m
117.5	117.5	118
81.4	81.4	81
41.9	41.9	42



Figure 2.6: ZX 300M ZX563 (right LiDAR in yellow) at the RSD verification location.

2.4 Data stream

The Meteorological Mast MM6 is connected via a glass fibre network to the measurement office at the EWTW test site. From here, the data are transported on a daily basis to the TNO offices in Petten, where they are stored on a server and imported in a dedicated Wind Data Management System (WDMS) database. The LiDAR data are accumulated in the LiDAR device itself.




Figure 2.7: Layout of the meteorological mast MM6

3 Data selection

The LiDAR measurement campaign officially starts on 12 October 2023 12:20 and ends on 5 December 2023 00:00 UTC. Figures 3.1 and 3.2 show the time series for the wind speed and wind direction measured by the reference meteorological mast and the LiDAR, prior to filtering.




Figure 3.1: Unfiltered wind speed time series for the comparison heights by the reference meteorological mast at the RSD verification location (top) and the LiDAR (bottom)

3.1 Filter criteria

The data is filtered in accordance with IEC 61400-50-2:2022 [1, clause 6.3, p.15]:

- a) *Reference meteorological mast free of wakes*
The measurement sector is defined in paragraph 2.3 and the filtering is applied to the wind direction measurements at each comparison height individually.
- b) *LiDAR free of wakes*
The LiDAR is located 49 m from the base of MM6. At 117.5 m MM6 is inside the (circular) measurement volume of the LiDAR. Due to the cone angle of the LiDAR, the radius of this circle increases with measurement height.




Figure 3.2: Unfiltered wind direction time series for various heights by the reference meteorological mast at the RSD verification location (top) and the LiDAR (bottom)

The resulting ratio between the wind speeds measured by MM6 and the LiDAR at each comparison height and within the measurement sector, does not show a strong directional dependency, see fig. A.1.

c) *Anemometers free of mast wake*

For measurement heights below the top cup, the influence of the MM6 wake on the reference cup anemometers is mitigated by combining measurements of two cups on booms at opposite sides of the mast.

d) *Icing*

The MEASNET [4] icing criterion is applied, which eliminates data if the temperature is below 2 °C while the relative humidity is over 80 %. The impact of this criterion is shown in fig. 3.3.

e) *Data availability*

For the LiDAR system no availability filtering is applied, other than the data that is being rejected by the LiDAR system itself.

f) *Precipitation*

The LiDAR performance might be affected by precipitation however no filtering on precipitation was undertaken. The IEC 61400-50-2:2022 describes that in general no filtering on precipitation should be applied unless specifically described by the manufacturers guidelines.




Figure 3.3: Filter: MEASNET icing criterion

4 LiDAR verification

This chapter reports the results of the LiDAR verification analysis as defined in clause 7 [1]. The analysis is performed using the in-house software tool *RSDverification* version 2.0.13.

4.1 Direct data comparison

A comparison of the horizontal wind speed between the meteorological mast devices and the LiDAR for each comparison height is presented in figs. 4.1 to 4.3. The format is taken from figure 6 [1]. Only samples for which the reference wind speed is in the range of 4 m/s to 16 m/s are used.

4.2 Bin-wise data comparison

The bin-wise comparison described in clause 7 [1] first requires binning of the reference wind speeds measured on the meteorological mast. The prescribed bin width is 0.5 m/s centred on integer multiples of 0.5 m/s. Because the range is 4 m/s to 16 m/s, the first and last bin are given half the prescribed width and are centred at 4.125 m/s and 15.875 m/s respectively.

The resulting bin count histograms are presented in fig. A.3. Due to the smaller bin width, the first and last bin have a significantly lower bin count.

The resulting bin-wise comparisons for each measurement height, are presented in figs. 4.4 to 4.6. The results of the regressions are summarised in table 4.1. The uncertainty intervals shown in these figures are discussed in section 6.2.

Table 4.1: LiDAR verification IEC 61400-50-2 results

height	slope	offset	R^2
m	–	m/s	–
117.5	0.997	-0.002	1.000
81.4	0.999	-0.032	1.000
41.9	1.006	-0.047	1.000

4.3 Systematic uncertainties

The results of the systematic uncertainty analysis, as described in section 6.2, are presented for each comparison height in tables 4.2 to 4.4. The tables are modelled after table 11 [1]. The total LiDAR uncertainty is reported in column ' V_{rsd} uncertainty'.

If there are fewer than three data sets in any bin, all statistics (mean and standard deviation) and derived properties are omitted from the table.

4.4 Environmental conditions

The uncertainty computation for the LiDAR as part of a future campaign requires the environmental conditions experienced during the LiDAR verification test [1, clause 11.1, item i].

The conditions at each comparison height are defined in chapter 5 and reported in tables 4.5 to 4.7. These tables covers all the measured environmental variables. However, the DNV-GL classification report [5] for the ZX300 LiDAR names seven significant environmental variables in the conclusion, among which ‘temperature gradient’ is not measured in this verification.

The environmental data is subject to the same filtering steps as the (wind speed) data used for the verification analysis. The environmental data is binned against the reference wind speed¹.

¹For the reference wind speed the bin centre is reported, because each environmental condition may have a slightly different bin-wise mean wind speed depending on the availability of environmental data.




Figure 4.1: Wind speed comparison @117.5 m




Figure 4.2: Wind speed comparison @81.4 m




Figure 4.3: Wind speed comparison @41.9 m




Figure 4.4: Bin-wise wind speed comparison @117.5 m




Figure 4.5: Bin-wise wind speed comparison @81.4 m




Figure 4.6: Bin-wise wind speed comparison @41.9 m

Table 4.2: Uncertainty calculations of the LiDAR @117.5 m

V_{ref}	V_{rsd}	data sets	$V_{rsd} \text{ max}$	$V_{rsd} \text{ min}$	$V_{rsd} \text{ std}$	$V_{rsd} \frac{std}{\sqrt{n}}$	mean deviation	$V_{ref} \text{ unc.}$	mounting unc. rsd	$V_{rsd} \text{ unc.}$
m/s	m/s	#	m/s	m/s	m/s	m/s	%	%	%	%
4.13	4.15	66	4.50	3.72	0.118	0.014	0.561	1.355	0.10	1.525
4.49	4.47	198	5.02	3.85	0.189	0.013	-0.400	1.280	0.10	1.392
4.99	4.98	158	5.46	4.15	0.200	0.016	-0.183	1.193	0.10	1.268
5.53	5.49	149	6.10	4.85	0.184	0.015	-0.719	1.120	0.10	1.377
6.00	5.97	169	6.58	4.82	0.208	0.016	-0.568	1.066	0.10	1.257
6.49	6.44	171	7.38	5.76	0.212	0.016	-0.621	1.022	0.10	1.242
6.99	6.97	165	8.03	6.25	0.242	0.019	-0.339	0.982	0.10	1.097
7.49	7.46	173	8.10	6.90	0.222	0.017	-0.386	0.949	0.10	1.072
8.00	7.97	174	8.98	7.13	0.276	0.021	-0.423	0.918	0.10	1.068
8.50	8.48	178	10.22	7.52	0.388	0.029	-0.229	0.893	0.10	1.008
8.97	8.97	161	10.01	8.09	0.294	0.023	-0.066	0.872	0.10	0.938
9.49	9.46	187	10.29	8.21	0.286	0.021	-0.364	0.855	0.10	0.981
10.01	10.00	160	11.46	9.41	0.282	0.022	-0.107	0.841	0.10	0.905
10.51	10.48	198	11.88	8.85	0.332	0.024	-0.277	0.829	0.10	0.930
10.99	10.94	217	11.60	10.21	0.226	0.015	-0.381	0.819	0.10	0.940
11.49	11.48	203	12.49	10.17	0.288	0.020	-0.108	0.809	0.10	0.865
11.98	11.93	163	12.70	11.01	0.261	0.020	-0.438	0.801	0.10	0.955
12.49	12.49	137	13.41	11.88	0.272	0.023	0.022	0.793	0.10	0.845
12.99	12.92	134	13.71	12.18	0.249	0.022	-0.601	0.786	0.10	1.028
13.48	13.39	131	14.20	12.16	0.293	0.026	-0.616	0.780	0.10	1.036
13.97	13.93	112	14.56	13.37	0.228	0.022	-0.325	0.773	0.10	0.882
14.52	14.46	109	15.13	13.93	0.262	0.025	-0.355	0.766	0.10	0.891
14.97	14.91	79	15.74	13.71	0.323	0.036	-0.453	0.761	0.10	0.945
15.48	15.47	77	16.48	14.46	0.336	0.038	-0.065	0.757	0.10	0.829
15.87	15.84	28	16.23	15.45	0.223	0.042	-0.180	0.753	0.10	0.849

Table 4.3: Uncertainty calculations of the LiDAR @81.4 m

V_{ref}	V_{rsd}	data sets	$V_{rsd} \text{ max}$	$V_{rsd} \text{ min}$	$V_{rsd} \text{ std}$	$V_{rsd} \frac{\text{std}}{\sqrt{n}}$	mean deviation	$V_{ref} \text{ unc.}$	mounting unc. rsd	$V_{rsd} \text{ unc.}$
m/s	m/s	#	m/s	m/s	m/s	m/s	%	%	%	%
4.12	4.10	95	4.34	3.81	0.107	0.011	-0.503	1.350	0.10	1.482
4.51	4.49	170	4.91	3.92	0.184	0.014	-0.552	1.277	0.10	1.443
4.98	4.94	191	5.59	4.48	0.185	0.013	-0.802	1.207	0.10	1.491
5.50	5.46	166	6.10	5.08	0.195	0.015	-0.554	1.154	0.10	1.329
6.00	5.97	181	6.57	5.25	0.193	0.014	-0.588	1.109	0.10	1.297
6.50	6.49	161	7.00	6.03	0.200	0.016	-0.206	1.062	0.10	1.131
6.99	6.95	171	7.52	6.24	0.211	0.016	-0.622	1.028	0.10	1.244
7.50	7.45	161	9.03	6.63	0.264	0.021	-0.705	0.991	0.10	1.267
8.01	7.98	180	9.05	7.32	0.227	0.017	-0.424	0.960	0.10	1.094
8.51	8.42	163	9.17	7.07	0.237	0.019	-1.106	0.943	0.10	1.486
8.98	8.94	182	9.83	8.24	0.252	0.019	-0.380	0.920	0.10	1.041
9.50	9.44	223	10.58	8.85	0.242	0.016	-0.609	0.914	0.10	1.134
9.99	9.92	208	10.45	8.46	0.279	0.019	-0.714	0.894	0.10	1.181
10.50	10.46	180	11.37	9.27	0.257	0.019	-0.336	0.881	0.10	0.986
10.97	10.92	177	11.68	10.05	0.267	0.020	-0.455	0.872	0.10	1.026
11.49	11.44	138	12.21	10.55	0.265	0.023	-0.429	0.864	0.10	1.009
12.00	11.92	139	12.76	11.12	0.266	0.023	-0.648	0.849	0.10	1.107
12.50	12.40	120	13.27	11.66	0.258	0.024	-0.762	0.842	0.10	1.173
13.01	12.94	88	13.75	12.49	0.264	0.028	-0.560	0.827	0.10	1.046
13.49	13.41	94	14.10	12.82	0.285	0.029	-0.601	0.825	0.10	1.067
13.99	14.00	73	15.10	13.43	0.331	0.039	0.062	0.818	0.10	0.895
14.49	14.49	61	15.20	13.90	0.281	0.036	-0.022	0.810	0.10	0.877
15.00	15.02	56	15.78	14.14	0.344	0.046	0.096	0.823	0.10	0.911
15.50	15.45	33	15.97	15.01	0.243	0.042	-0.309	0.799	0.10	0.926
15.87	15.78	18	16.28	15.35	0.210	0.050	-0.565	0.791	0.10	1.046

Table 4.4: Uncertainty calculations of the LiDAR @41.9 m

V_{ref}	V_{rsd}	data sets	$V_{rsd} \text{ max}$	$V_{rsd} \text{ min}$	$V_{rsd} \text{ std}$	$V_{rsd} \frac{std}{\sqrt{n}}$	mean deviation	$V_{ref} \text{ unc.}$	mounting unc. rsd	$V_{rsd} \text{ unc.}$
m/s	m/s	#	m/s	m/s	m/s	m/s	%	%	%	%
4.13	4.13	111	4.76	3.82	0.124	0.012	-0.032	1.381	0.10	1.428
4.50	4.49	239	5.04	3.91	0.200	0.013	-0.120	1.313	0.10	1.368
5.02	5.03	202	5.77	4.24	0.207	0.015	0.180	1.229	0.10	1.295
5.47	5.47	193	6.22	4.90	0.218	0.016	0.081	1.173	0.10	1.230
6.02	6.02	193	6.76	5.45	0.233	0.017	-0.004	1.111	0.10	1.167
6.49	6.50	210	7.28	5.82	0.219	0.015	0.141	1.067	0.10	1.124
6.99	6.97	192	7.71	5.70	0.263	0.019	-0.286	1.031	0.10	1.127
7.49	7.50	190	8.12	6.79	0.266	0.019	0.057	0.997	0.10	1.055
7.99	7.97	217	8.76	7.10	0.260	0.018	-0.264	0.971	0.10	1.054
8.48	8.49	186	9.55	7.85	0.287	0.021	0.123	0.940	0.10	1.005
9.01	9.03	190	10.27	8.05	0.295	0.021	0.170	0.921	0.10	0.991
9.48	9.49	151	10.52	8.83	0.281	0.023	0.049	0.910	0.10	0.969
10.01	10.00	138	10.87	8.99	0.311	0.026	-0.158	0.888	0.10	0.966
10.50	10.52	139	11.29	9.74	0.293	0.025	0.196	0.875	0.10	0.954
10.98	10.95	125	11.87	9.88	0.343	0.031	-0.273	0.874	0.10	0.983
11.50	11.52	113	12.25	10.73	0.328	0.031	0.144	0.852	0.10	0.932
11.97	11.99	85	13.06	10.71	0.396	0.043	0.164	0.854	0.10	0.967
12.47	12.55	70	13.25	11.71	0.339	0.040	0.627	0.844	0.10	1.123
12.99	12.97	49	13.81	12.21	0.376	0.054	-0.100	0.840	0.10	0.968
13.45	13.45	50	14.36	12.68	0.347	0.049	0.049	0.831	0.10	0.936
14.01	14.00	39	14.72	13.39	0.380	0.061	-0.058	0.824	0.10	0.960
14.51	14.52	30	15.28	13.76	0.326	0.059	0.050	0.812	0.10	0.938
15.00	14.95	30	15.76	14.40	0.333	0.061	-0.310	0.800	0.10	0.975
15.41	15.42	18	16.21	15.03	0.286	0.067	0.070	0.791	0.10	0.934
15.85	16.19	2	16.19	16.18	0.007	0.005	2.132	0.770	0.10	2.278

Table 4.5: Environmental conditions @117.5 m

wind speed	shear exponent	turbulence intensity	precipitation	wind direction	air temperature	relative humidity	air density	flow inclination	wind veer
m/s	–	%	%	°	°C	%	kg/m ³	°	°/m
4.125	0.1715	7.23	7.13	241.8	8.27	82.29	1.230	0.912	-0.2343
4.500	0.2201	7.18	11.57	248.5	8.32	81.43	1.231	0.830	-0.2193
5.000	0.2324	6.85	13.08	248.2	8.43	80.76	1.228	0.969	-0.1773
5.500	0.2839	8.12	11.83	257.1	8.40	81.20	1.226	1.002	-0.1747
6.000	0.2959	8.11	7.34	254.5	8.74	81.53	1.221	0.942	-0.1499
6.500	0.2954	7.94	7.68	255.2	8.82	81.23	1.221	0.989	-0.1358
7.000	0.2869	8.56	11.96	255.4	8.95	80.84	1.223	1.049	-0.1052
7.500	0.2883	8.09	11.28	242.7	9.34	81.88	1.218	1.053	-0.1055
8.000	0.2808	8.83	16.94	257.9	9.40	79.26	1.219	1.133	-0.1044
8.500	0.2884	9.11	14.85	254.2	9.68	79.39	1.217	1.123	-0.1016
9.000	0.2783	8.56	16.01	239.0	9.69	81.85	1.215	1.113	-0.0952
9.500	0.2715	9.14	20.68	241.1	9.57	80.48	1.216	1.079	-0.0771
10.000	0.2760	8.98	19.71	240.1	9.58	80.44	1.219	1.148	-0.0706
10.500	0.2566	8.99	15.94	235.8	9.74	82.64	1.216	1.052	-0.0599
11.000	0.2568	8.97	15.29	240.0	9.64	81.27	1.217	0.988	-0.0540
11.500	0.2441	9.77	18.13	236.0	9.94	82.44	1.213	1.002	-0.0483
12.000	0.2339	10.02	24.39	236.4	10.06	81.71	1.211	0.965	-0.0427
12.500	0.2320	10.10	18.56	248.0	9.73	80.07	1.213	1.071	-0.0432
13.000	0.2281	10.16	23.75	245.3	9.98	82.16	1.211	1.062	-0.0379
13.500	0.2221	10.57	20.14	249.1	10.39	81.51	1.209	1.145	-0.0369
14.000	0.2237	10.62	22.66	248.5	10.31	82.36	1.212	1.193	-0.0364
14.500	0.2213	10.32	25.34	239.4	10.68	82.52	1.207	1.144	-0.0346
15.000	0.2104	10.15	18.76	233.3	10.69	81.89	1.204	1.035	-0.0341
15.500	0.2149	10.73	18.01	237.3	11.83	80.69	1.201	1.092	-0.0336
15.875	0.2253	10.47	7.53	230.4	12.98	77.80	1.194	1.064	-0.0332

Table 4.6: Environmental conditions @81.4 m

wind speed	shear exponent	turbulence intensity	precipitation	wind direction	air temperature	relative humidity	air density	flow inclination	wind veer
m/s	–	%	%	°	°C	%	kg/m ³	°	°/m
4.125	0.1668	8.08	7.23	237.0	8.07	80.40	1.231	0.889	-0.1978
4.500	0.2072	7.66	18.01	235.6	8.58	81.72	1.227	0.923	-0.1769
5.000	0.2401	7.92	12.12	239.2	8.53	80.40	1.227	0.966	-0.1592
5.500	0.2689	8.63	8.83	239.8	8.70	81.64	1.222	0.844	-0.1445
6.000	0.2649	8.65	9.77	240.5	8.87	82.37	1.221	0.865	-0.1178
6.500	0.2677	8.93	12.35	240.3	8.86	80.89	1.219	0.983	-0.1168
7.000	0.2837	9.92	12.87	245.3	9.50	80.31	1.217	1.039	-0.0993
7.500	0.2655	9.95	15.29	241.7	9.52	80.93	1.218	1.020	-0.0931
8.000	0.2756	9.41	17.05	230.8	9.83	81.76	1.214	0.994	-0.1045
8.500	0.2726	9.57	19.06	236.0	9.87	79.42	1.214	1.033	-0.0909
9.000	0.2584	10.34	21.27	232.4	9.76	81.85	1.215	1.078	-0.0718
9.500	0.2665	10.26	13.63	236.5	9.92	80.98	1.217	1.051	-0.0583
10.000	0.2481	10.65	17.16	231.2	9.59	83.28	1.216	0.996	-0.0553
10.500	0.2348	11.35	24.90	228.8	9.60	83.72	1.214	0.936	-0.0445
11.000	0.2290	10.94	17.78	229.1	10.08	82.20	1.211	0.862	-0.0410
11.500	0.2145	11.36	24.49	232.5	10.08	81.19	1.211	0.912	-0.0406
12.000	0.2162	11.80	19.39	239.7	10.65	82.32	1.207	1.053	-0.0360
12.500	0.2263	11.66	22.27	238.3	10.64	83.25	1.207	1.073	-0.0373
13.000	0.2125	12.07	26.85	237.8	11.14	83.45	1.203	1.054	-0.0347
13.500	0.2198	11.83	15.91	237.8	11.37	82.69	1.205	1.130	-0.0342
14.000	0.2158	11.76	20.63	221.3	11.79	81.61	1.197	1.014	-0.0350
14.500	0.2054	11.72	10.10	222.7	12.97	79.52	1.193	0.915	-0.0350
15.000	0.2056	12.22	12.04	244.9	11.71	78.34	1.203	0.857	-0.0361
15.500	0.2042	12.54	1.12	253.7	13.17	76.39	1.198	1.212	-0.0341
15.875	0.2094	13.09	8.47	250.9	13.11	78.27	1.198	1.308	-0.0287

Table 4.7: Environmental conditions @41.9 m

wind speed	shear exponent	turbulence intensity	precipitation	wind direction	air temperature	relative humidity	air density	flow inclination	wind veer
m/s	–	%	%	°	°C	%	kg/m ³	°	°/m
4.125	0.1756	8.88	12.58	232.0	8.53	79.26	1.227	0.931	-0.2117
4.500	0.1938	9.45	11.82	234.9	8.60	80.66	1.225	1.041	-0.1755
5.000	0.2207	10.22	12.31	228.8	8.62	81.86	1.222	0.879	-0.1226
5.500	0.2485	11.14	10.50	228.5	9.22	82.68	1.218	0.887	-0.0901
6.000	0.2614	11.83	11.21	236.4	9.49	81.27	1.216	1.052	-0.1010
6.500	0.2634	11.37	14.26	230.9	9.67	79.80	1.216	1.040	-0.1085
7.000	0.2496	11.68	14.19	225.6	9.97	79.14	1.215	1.069	-0.0983
7.500	0.2598	12.80	25.01	229.3	9.64	81.02	1.216	1.055	-0.0665
8.000	0.2582	12.53	15.03	234.7	9.76	81.10	1.218	1.031	-0.0529
8.500	0.2355	13.18	27.27	225.0	9.48	84.70	1.216	0.971	-0.0487
9.000	0.2375	13.64	23.24	235.3	9.66	82.31	1.214	0.993	-0.0446
9.500	0.2209	13.25	20.83	225.0	9.81	84.29	1.212	0.892	-0.0411
10.000	0.2238	13.52	26.73	232.9	10.46	82.13	1.209	1.024	-0.0410
10.500	0.2161	13.70	18.98	235.5	10.67	82.32	1.208	1.017	-0.0354
11.000	0.2100	13.91	19.71	240.4	10.86	82.71	1.207	1.083	-0.0337
11.500	0.2136	13.91	17.45	232.8	11.58	81.36	1.201	1.078	-0.0342
12.000	0.2065	13.98	17.31	238.1	11.74	79.96	1.202	1.141	-0.0334
12.500	0.2096	13.69	22.03	237.0	12.09	80.76	1.200	1.128	-0.0355
13.000	0.1964	14.10	9.23	221.1	12.37	78.28	1.198	0.885	-0.0340
13.500	0.1909	13.57	4.03	241.2	12.25	77.42	1.200	0.891	-0.0324
14.000	0.1937	14.20	13.17	255.6	12.13	77.01	1.203	1.186	-0.0289
14.500	0.1953	13.80	3.76	254.7	12.24	75.68	1.203	1.214	-0.0292
15.000	0.1897	14.09	17.11	247.7	13.32	78.28	1.197	1.203	-0.0295
15.500	0.1918	13.94	10.09	248.4	13.00	77.47	1.196	1.282	-0.0308
15.875	0.2034	15.01	76.83	219.9	18.76	81.32	1.169	1.361	-0.0330

5 Sensitivities

This chapter investigates the sensitivity of the LiDAR measurement for various environmental variables (EVs). The sensitivity analysis is performed in accordance with the classification analysis specified in clause 6 [1]. However, for this analysis we use the same dataset as for the verification analysis. As a result the wind speed range is restricted to 4 m/s to 16 m/s.

5.1 Sensitivity analysis

The basis of this analysis is the deviation between the wind speeds measured by the ref, v_{ref} , and the rsd, v_{rsd} . The deviation is defined in eq. (5.1). Subsequently the sensitivity of this deviation is tested against various EVs. The list of variables is based on table 4 [1]. The variables considered are described below.

$$\text{deviation} = \frac{v_{ref} - v_{rsd}}{v_{rsd}} \quad (5.1)$$

Unless stated otherwise the EVs are height-independent, meaning the same value was used for the sensitivity analysis at each comparison height.

1. Shear exponent [-]

The shear exponent, α , is computed by fitting a power law wind shear model through the v_{ref} measurements at 41.9 m, 81.4 m and 117.5 m. For the wind shear, the top cup measurement is combined with the mast flow distortion corrected [6] signals for the boom mounted cup measuring heights 41.9 m and 81.4 m. This way the measurements at all heights are effectively undisturbed. The power law is defined by

$$\frac{v_{ref}}{v_r} = \left(\frac{h}{h_r} \right)^\alpha \quad (5.2)$$

2. Reference turbulence intensity [-]

The reference turbulence intensity, measured on the meteorological mast, is defined by

$$\text{reference turbulence intensity} = \frac{\text{std}(v_{ref})}{\text{mean}(v_{ref})} \cdot 100 \% \quad (5.3)$$

This variable is height-dependent.

3. Precipitation [%]

The rain sensor returns a 0 % to 100 % signal indicating the amount of time precipitation was detected in the 10-minute interval. The precipitation is measured at 40 m.

4. Reference wind direction [°]

The wind direction, as measured on the meteorological mast, is height-dependent.

5. Air temperature [°C]

The air temperature is measured at 109 m.

6. Relative humidity [%RH]

The relative humidity is measured at 109 m. (The relative humidity was added to the list of EVs, because it is used in the MEASNET icing criterion in chapter 3.)

7. Air density [kg/m³]

The air density is computed from the air pressure, air temperature and relative humidity, all measured at 109 m, in accordance with equation (12) of IEC 61400-12-1:2022.

8. Flow inclination [°]

The flow inclination is defined as

$$\text{flow inclination} = \arctan \left(\frac{v_{\text{vert}}}{v_{\text{hor}}} \right) \quad (5.4)$$

The horizontal (v_{hor}) and vertical (v_{vert}) wind speed components are measured by a sonic anemometer at a height of 108.5 m.

9. Wind veer [°/m]

The wind veer is computed as the difference between the wind direction measurements by meteorological mast at 37.9 m and 112.5 m, divided by the height difference. This definition was taken from IEC 61400-12-1:2022.

$$\text{wind veer} = \frac{w_{d,37.9} - w_{d,112.5}}{112.5 - 37.9} \quad (5.5)$$

10. Reference wind speed [m/s]

This wind speed, as measured on the meteorological mast, is height-dependent.

The sensitivity analysis leads to the results presented in table 5.2, which is presented in the same format as table 4 [1]. In this table column ‘ m ’ represents the slope of the two-parameter regression of the bin-wise averaged data. Column ‘ r^2 ’ represents the correlation coefficient of the two-parameter regression of the scatter data.

For the computation of the bin-wise averages, only those bins are included that meet the following bin-count requirement, stipulated by the criterion in eq. (5.6) [1, eq. 3]. When the reference wind speed is used as the EV, also the criterion in equation (4) needs to be applied.

$$n_i > \frac{N}{2 \cdot n_b} \quad (5.6)$$

The sensitivity, presented in column ‘sens.’, is defined by

$$\text{sensitivity} = m \cdot \text{std} \quad (5.7)$$

where ‘std’ is the standard deviation of the EV data.

The sensitivity of the LiDAR for an EV is considered as significant if either the sensitivity exceeds a value of 0.5, or the product of sensitivity and r exceeds 0.1. In table 5.2, the sensitivity criteria that exceed their threshold value are highlighted in red. In case a significant sensitivity for an EV is observed for at least one comparison height, that EV must be considered as significant for all comparison heights. Table 5.1 shows that none of the environmental variables result in a significant sensitivity. The distribution of the environmental variables is shown in table 5.4.

5.2 Impact on accuracy

The basis for the accuracy class is the product of m , as already presented in table 5.2, and the range of the EV. Although our interest is not in determining the accuracy class, we are

Table 5.1: Overview of significant sensitivities, '-' means the environmental variable is not significant.

environmental variable	comparison height			overall
	117.5m	81.4m	41.9m	
shear exponent	-	-	-	-
turbulence intensity	-	-	-	-
precipitation	-	-	-	-
wind direction	-	-	-	-
air temperature	-	-	-	-
relative humidity	-	-	-	-
air density	-	-	-	-
flow inclination	-	-	-	-
wind veer	-	-	-	-
reference wind speed	-	-	-	-

interested in the effect of the significant sensitivities. However, as presented in section 5.1, no significant sensitivities are found. The EV ranges are largely prescribed by table 5 [1]. The results are presented in table 5.3, which is presented in a similar format as table 8 [1].

The range is a defined quantity, presented in the column 'range' of table 5.3. The IEC 61400-50-2 standard defines the measured range of variation through the ratio of bins that meet the criterion in eq. (5.6). The result is presented in the column 'covered range'. The measured range of variation is considered sufficient if the covered range is at least 25 %.

For the relative humidity no range is prescribed; we used 0 % to 100 %.

The EV air density, for all heights, does not meet the range requirement. This is caused by the limited variation of air density at the site with respect to the prescribed range.

The last column of table 5.3 represents the contribution to the preliminary accuracy class for each EV. From this we can draw the conclusion that shear has the highest influence on the accuracy.

Table 5.2: Sensitivity to environmental variables for the LiDAR

variable	unit	height	avg	std	m	sens.	R^2	sens. $\times R$
		m	unit	unit	%/unit	%	-	%
shear exponent		41.9	0.24	0.08	0.893	0.070	0.002	0.003
		81.4	0.25	0.08	-4.849	-0.396	0.034	-0.073
		117.5	0.26	0.09	-5.122	-0.461	0.038	-0.090
turbulence intensity	%	41.9	12.09	2.43	0.050	0.121	0.003	0.006
		81.4	9.63	2.85	0.051	0.144	0.005	0.010
		117.5	8.49	2.69	0.054	0.145	0.005	0.010
precipitation [†]	%	41.9	16.83	32.74	0.003	0.096	0.000	0.000
		81.4	16.28	32.53	0.007	0.212	0.001	0.005
		117.5	15.87	31.96	0.010	0.310	0.006	0.023
wind direction	°	41.9	232.76	48.70	0.000	0.019	0.000	0.000
		81.4	236.68	50.53	-0.005	-0.271	0.032	-0.049
		117.5	245.91	53.94	-0.005	-0.291	0.023	-0.044
air temperature	°C	41.9	9.70	2.42	0.010	0.025	0.000	0.000
		81.4	9.58	2.41	0.034	0.082	0.000	0.001
		117.5	9.37	2.37	-0.009	-0.020	0.000	0.000
relative humidity	%	41.9	81.55	9.65	0.011	0.101	0.000	0.002
		81.4	81.65	9.73	0.016	0.152	0.007	0.013
		117.5	81.26	9.82	0.032	0.314	0.024	0.049
air density	kg/m ³	41.9	1.21	0.02	-5.408	-0.100	0.001	-0.002
		81.4	1.21	0.02	-6.244	-0.113	0.005	-0.008
		117.5	1.22	0.02	-3.983	-0.073	0.005	-0.005
flow inclination	°	41.9	1.04	0.51	0.160	0.081	0.000	0.001
		81.4	0.99	0.54	-0.359	-0.194	0.009	-0.018
		117.5	1.07	0.55	-0.314	-0.173	0.006	-0.013
wind veer	°/m	41.9	-0.05	0.03	3.257	0.100	0.001	0.003
		81.4	-0.06	0.04	8.162	0.327	0.022	0.049
		117.5	-0.06	0.04	6.337	0.257	0.016	0.032
reference wind speed	m/s	41.9	7.39	2.09	0.002	0.003	0.000	0.000
		81.4	8.47	2.60	-0.002	-0.006	0.000	0.000
		117.5	9.23	3.00	-0.004	-0.013	0.000	0.000

› The sensitivity, computed as $m \times \text{std}$, is reported in column 'sens.'

› The values for 'avg', 'std' and R^2 are derived from a regression of the 10-minute data contained in the bins that have a statistically significant bin-count, while m is the slope derived from a regression of the bin-wise mean values [1, p.18-19]. (As a result, no slope - and by extension no sensitivity - can be computed for variables that only yield a single bin with a significant bin-count.)

› An environmental variable is considered significant if either the sensitivity exceeds the value of 0.5 %, or the product of the sensitivity and the correlation coefficient of the regression (sensitivity $\times R$), reported in the ultimate column, exceeds the value of 0.1 % [1, Clause 6.5]. The numbers in these columns are highlighted in orange if they cause the variable to be considered significant, otherwise they are blue.

† These variables employ a modified bin-count criterion [1, eq. 3, p.18]. In order to allow for a sensitivity analysis, the number of data points (N) is reduced to those data points that have a non-zero value.

Table 5.3: Maximum influence of environmental variables on the LiDAR wind speed

variable	unit	min	max	bin	range	height	covered	$m \times \text{range}$
		unit	unit	unit	unit	m	%	%
shear exponent		-0.4	0.8	0.05	1.2	41.9	33	1.072
						81.4	33	-5.818
						117.5	38	-6.146
turbulence intensity	%	3	24	1	21	41.9	52	1.047
						81.4	57	1.064
						117.5	52	1.130
precipitation	%	0	100	10	100	41.9	100	0.294
						81.4	100	0.653
						117.5	100	0.968
wind direction	°	0	360	5	180	41.9	42	0.071
						81.4	43	-0.966
						117.5	49	-0.971
air temperature	°C	0	40	2	40	41.9	30	0.404
						81.4	30	1.356
						117.5	30	-0.344
relative humidity	%	0	100	10	100	41.9	40	1.051
						81.4	40	1.560
						117.5	40	3.194
air density	kg/m ³	0.9	1.35	0.05	0.45	41.9	22	-2.433
						81.4	22	-2.810
						117.5	22	-1.792
flow inclination	°	-3	3	0.2	6	41.9	40	0.959
						81.4	43	-2.155
						117.5	43	-1.884
wind veer	°/m	-0.3	0.1	0.04	0.4	41.9	40	1.303
						81.4	50	3.265
						117.5	50	2.535
reference wind speed	m/s	4	16	0.5	12	41.9	62	0.019
						81.4	79	-0.026
						117.5	92	-0.051

- › The columns 'min', 'max' and 'bin' report the minimum and maximum value of the binning interval [1, Table 5, p.21], and the bin width [1, Table 3, p.18], used for the regression. The 'range' columns reports the expected natural range of variation for each environmental variable.
- › The column 'covered' reports the percentage of the range that was covered by bins that meet the bin-count criteria of equations (3) and (4) [1, p.18-19]. If the covered range is less than 25 %, the sensitivity results for this environmental variable are considered unrepresentative. Unrepresentative covered ranges are highlighted in orange, otherwise they are blue.
- › The product of m , the slope of the regression reported in table 5.2, and the full range of variation, reported in the ultimate column, represents the maximum influence an environmental variable can have on the uncertainty of the horizontal wind speed. Note that this result is highly dependent on the chosen range value, which may be far greater than the variations actually observed during the campaign.

Table 5.4: Distribution of environmental variables used in the LiDAR sensitivity study

variable	unit	height	min	Q1	median	Q3	max
		m	unit	unit	unit	unit	unit
shear exponent		41.9	-2.00	0.14	0.22	0.29	1.31
		81.4	-2.00	0.14	0.22	0.29	1.31
		117.5	-2.00	0.14	0.22	0.29	1.31
turbulence intensity	%	41.9	1.68	10.30	12.40	14.07	41.72
		81.4	1.83	7.73	10.12	12.18	43.54
		117.5	1.44	6.42	8.71	10.99	48.66
precipitation	%	41.9	0.00	0.00	0.00	0.00	100.00
		81.4	0.00	0.00	0.00	0.00	100.00
		117.5	0.00	0.00	0.00	0.00	100.00
air temperature	°C	41.9	-1.15	7.07	9.39	10.99	20.20
		81.4	-1.15	7.07	9.39	10.99	20.20
		117.5	-1.15	7.07	9.39	10.99	20.20
relative humidity	%	41.9	49.48	75.08	84.14	92.93	101.26
		81.4	49.48	75.08	84.14	92.93	101.26
		117.5	49.48	75.08	84.14	92.93	101.26
air density	kg/m ³	41.9	1.17	1.20	1.22	1.24	1.28
		81.4	1.17	1.20	1.22	1.24	1.28
		117.5	1.17	1.20	1.22	1.24	1.28
flow inclination	°	41.9	-22.33	0.17	0.80	1.30	24.14
		81.4	-22.33	0.17	0.80	1.30	24.14
		117.5	-22.33	0.17	0.80	1.30	24.14
wind veer	°/m	41.9	-2.19	-0.11	-0.05	-0.03	2.05
		81.4	-2.19	-0.11	-0.05	-0.03	2.05
		117.5	-2.19	-0.11	-0.05	-0.03	2.05
reference wind speed	m/s	41.9	4.00	5.87	7.83	10.13	15.90
		81.4	4.00	6.38	8.88	11.11	15.96
		117.5	4.00	6.74	9.43	11.84	15.99

- › The lower and upper quartiles are indicated by Q1 and Q3. The minimum, median and maximum values represent Q0, Q2 and Q4. These quartiles indicate below what value 0 %, 25 %, 50 %, 75 % and 100 % of the data is found.
- › The filters described in section 3.1 are only applied to the wind-related variables: rsd availability, reference wind speed, wind direction and - by extension - shear exponent, wind veer and turbulence intensity. All other variables are not filtered.
- › All wind-related variables data is discarded when the wind speed is less than 2 m/s. At very low wind speeds, differences in the measured wind speed between the LiDAR and the reference meteorological mast lead to high percentage deviations that could skew the sensitivity regression. This filtering also causes the reference wind speed variable to not contain values below 2 m/s.
- › Wind direction is omitted from this table, because it is a directional quantity.

6 Uncertainty

This chapter describes the uncertainty contributions to the horizontal wind speed measurement that were taken into account. These uncertainties are the basis for the LiDAR verification analysis reported in chapter 4. The uncertainty analysis is performed for application in the verification analysis only, therefore the uncertainty analysis is limited to the (horizontal) wind speed measurements.

All uncertainties are reported with a coverage factor of one ($k = 1$). To obtain uncertainties for $k = 2$ the results have to be doubled.

6.1 Reference devices - cup anemometers

The following contributions to the systematic uncertainty of the cup anemometers are taken into account in accordance with Clause 8.2 [1].

1. **Wind tunnel calibration**

The wind tunnel uncertainty, with a coverage factor of two ($k = 2$), is found in the wind tunnel calibration reports, see section B.1. The standard uncertainty ($k = 1$) is therefore the reported uncertainty divided by two.

2. **Effects according to anemometer classification**

The classification of the Thies First Class Advanced cup anemometer is 0.9S (heating on), see section B.2 for the classification results according the IEC 61400-50-1:2022 [7]. The uncertainty in the wind speed due to operational characteristics therefore is

$$u_{VS,class,i} = [0.5 \% + 0.05 \text{ m/s}] \cdot \frac{0.9}{\sqrt{3}}$$

3. **Mounting effects**

The default values for the uncertainty associated with the mounting of the anemometer on mast are specified in Annex E.6.3.5 [8]. At the height of 117.5 m a top mounted anemometers is used, for which the default uncertainty is

$$u_{VS,mnt,i} = 0.5 \%$$

At all other comparison heights, side-mounted anemometers are used. Normally this results in a 1.5 % mounting uncertainty, however for the verification the ‘true wind speed’ pseudo signals are used which make use of mast flow corrected wind speed signals. For flow corrected wind speed signals the uncertainty is determined by the root-sum-square of half the mean correction applied to the wind speed signal and 0.5 % of the measured signal. Wake sectors are excluded. So the uncertainty is at least 0.5 %.

$$u_{VS,mnt,i} \geq 0.5 \%$$

4. **Data acquisition**

The cup is connected to a digital pulse counting module. The uncertainty of the module together with the anemometer calibration factors lead to the following uncertainty.

$$u_f = 0.1 \% \cdot F + 0.5 \text{ Hz}.$$

Table B.3 shows that the gains of all Thies cup anemometers are close to 0.046 m/s/Hz. This results in an uncertainty of the wind speed of

$$u_{d,VS,i} = 0.1 \% + 0.023 \text{ m/s}.$$

The total systematic uncertainty of the reference sensor is obtained by adding all contributions in quadrature. As in IEC 61400-50-2, this is referred to as ‘reference type B’ uncertainty in fig. A.2.

6.2 Remote sensing device

The following contributions to the uncertainty of the LiDAR wind speed measurements are taken into account in accordance with clause 8.3 [1].

1. Systematic uncertainty of the reference sensor

This is the systematic uncertainty of the cup anemometer as defined in section 6.1.

2. Mean deviation

No correction of the LiDAR wind speed measurement is performed. Therefore, this contribution is defined as the bin-wise average deviation between the reference sensor and the LiDAR.

3. Standard uncertainty of the LiDAR measurements

The standard uncertainty is defined by eq. (6.1).

$$\text{standard uncertainty}_i = \frac{\sigma_{v_i}}{\sqrt{n_i}} \quad (6.1)$$

Where σ_{v_i} is the standard deviation of 10-minute average measurements in wind speed bin i and n_i is the bincount.

4. Mounting effects of the LiDAR

We are using the default magnitude stated in clause E.7.5 [8, p.74].

$$u_{VR,mnt,i} = 0.1 \%$$

The mounting uncertainty is reported in tables 4.2 to 4.4.

5. Non-homogeneous flow

The uncertainty due to non-homogeneous flow in the measurement volume of the LiDAR is estimated from a terrain flow assessment [9] based on the terrain information shown in fig. 2.2.

$$u_{VR,flow,i} = 0.2 \%$$

As the separation distance does not compromise the criteria as stated in clause 6.2, item d [1, p.14], no additional uncertainty contribution is taken into account.

The total LiDAR uncertainty is obtained by adding in quadrature the contributions above. The result is reported in the last column of tables 4.2 to 4.4. An overview of the various uncertainty contributions is presented in fig. A.2.

The uncertainty interval shown in figs. 4.4 to 4.6 is also obtained by adding in quadrature the contributions above, but with the exception of the mean deviation.

7 Deviations

The LiDAR verification as presented in chapter 4 is performed in accordance with IEC 61400-50-2:2022. For this verification campaign the following deviations are noted.

1. The highest wind bin for comparison height 41.9 m is included in the analysis with an insufficient bin count of 2, as the minimum requirement is 3 data sets per wind bin. This low bin count explains the high deviation in fig. 4.6.

8 Conclusions

The Wind@Sea LiDAR ZX 300M ZX563 is validated against reference meteorological mast MM6 at the RSD verification location at the EWTW test site in the Wieringermeer. In this campaign the LiDAR is validated at three measurement heights ranging from 42 m to 118 m.

During the measurement campaign that ran from 12 October 2023 12:20 UTC until 5 December 2023 00:00, spanning 53 days, all data coverage requirements of the IEC 61400-50-2:2022 are met, except for the highest wind speed bin for the lowest measuring height, 42 m, for which the bin count is 2 instead of the minimum required bin count of 3.

For all comparison heights the regression slope is close to 1.00 and the offset is up to 0.05 m/s with an R^2 close to 1. The LiDAR system underestimates the wind speed by up to 2.1 %. The sensitivity analysis did not result in any significant sensitivities for the LiDAR. For the air density at all comparison heights the range covered was insufficient.

References

- [1] IEC 61400-50-2:2022-08. *Wind energy generation systems – Part 50-2: Wind measurement – Application of ground-mounted remote sensing technology*. Aug. 2022.
- [2] G. Bergman and J.P. Verhoef. *TNO Ground Based RSD Verification Facility*. TNO 2020 R10781. TNO, July 2020.
- [3] IEC 61400-12-5:2022-10. *Wind energy generation systems – Part 12-5: Power performance – Assessment of obstacles and terrain*. Oct. 2022.
- [4] *Power performance measurement procedure - Version 5*. MEASNET, Dec. 2009.
- [5] T. Rafael. *TYPE ZX300 LIDAR - Remote Sensing Device Type-specific Classification Summary*. GLGH-4275 18 14741 258-R-0003. Version Rev. D. DNV GL - Energy, Nov. 9, 2018.
- [6] P. Werff and G. Bergman. *Correction of the wind speed for flow distortion by the met mast*. TNO 2019 M10121. TNO, Nov. 2019.
- [7] IEC 61400-50-1:2022-11. *Wind energy generation systems – Part 50-1: Wind measurement – Application of meteorological mast, nacelle and spinner mounted instruments*. Nov. 2022.
- [8] IEC 61400-12-1:2022-09. *Wind energy generation systems – Part 12-1: Power performance measurements of electricity producing wind turbines*. Sept. 2022.
- [9] D. A. J. Wouters. *Non-homogeneous flow within a lidar measurement volume at EWTW*. TNO 2019 M10109. ECN part of TNO, Jan. 2019.
- [10] G. Bergman, J. Schoorl, and F. Danzl. *Meteorological Mast 6 (lowered 2022) at EWTW, Instrumentation Report*. TNO 2022 R10731. TNO, Nov. 2022.

Signature

	Date: March 2024		Report number: TNO 2024 R10316
Title	Verification of the Wind@Sea LiDAR system ZX563 at the EWTW test site near meteorological mast MM6 Period: 12 October 2023 to 5 December 2023		
Author(s)	C. Liu and G. Bergman		
Principal(s)	Ministry of Economic Affairs and Climate (EZK)		
Project number	060.55419		
Programme(s)	Wind Energy		
Abstract	As part of a LiDAR verification campaign a ZX Lidars LiDAR with serial number ZX563 was deployed near MM6 at the EWTW test site in the Wieringermeer. This report describes the verification campaign for the LiDAR.		
Keywords	Wind@Sea, ZX 300M, ECN Wind Turbine test site Wieringermeer, LEG, LiDAR, verification		
Task	Name	Role	Signature
Author	C. Liu	Data analyst	
Expert review	D.A.J. Wouters	Data analyst	
Generic review	C.B.H. Eckels	Project manager	
Approval	R.H.M. Giepman	Deputy research manager	
Authorization	E.D. Nennie	Research manager	

Appendix A

IEC visualisations

This appendix contains visualizations associated with the IEC analysis reported in chapters 4 and 5 that are not a reporting requirement.




Figure A.1: Influence of the wake of meteorological mast on the LiDAR. The ratio of the wind speed measured by the LiDAR (w_{rsd}) and the reference meteorological mast MM6 (w_{ref}) is plotted against the wind direction measured by the reference meteorological mast. The blue line marks the direction for which the wind flows over the reference meteorological mast MM6 towards the LiDAR. The orange squares are the bin-wise average wind speed ratios; these are solid only if the respective bin contains a statistically significant number of data points.




Figure A.2: Contributions to the LiDAR uncertainty




Figure A.3: Histograms for bin-wise wind speed comparison

Appendix B

Instrumentation details

This appendix presents detailed information about the meteorological mast signals and sensors used. More detailed information about meteorological mast MM6 can be found in the meteorological mast instrumentation report [10].

At the meteorological mast measurement heights, as seen in fig. 2.7, the meteorological mast measurements are compared to the LiDAR measurements. Table B.1 lists these comparison heights and the wind speed and wind direction signals used from both the meteorological mast and the LiDAR. All of these signals are 10-minute average statistics.

Some of the statistics are directly derived from measured signals, presented in table B.2. Other statistics are based on pseudo signals, presented in table B.4, which are calculated signals.

The sensors used to measure these signals and the data acquisition modules they are attached to are listed in table B.3. This table also presents installation and calibration due dates.

Table B.1: Signals used for each comparison height

height (m)	met mast	LiDAR
	wind speed	
117.5	MM6_H117d5_Ws_Q1_avg	Horizontal Wind Speed (m/s) at 118m
81.4	MM6_H081d4_Ws_True_Q1_avg	Horizontal Wind Speed (m/s) at 81m
41.9	MM6_H041d9_Ws_True_Q1_avg	Horizontal Wind Speed (m/s) at 42m
	wind direction	
117.5	MM6_H112d5B320_Wd_Q1_avg	Wind Direction (deg) at 118m
81.4	MM6_H077d4B320_Wd_Q1_avg	Wind Direction (deg) at 81m
41.9	MM6_H037d9B320_Wd_Q1_avg	Wind Direction (deg) at 42m

Table B.2: List of measured signals

name	location	short name	sensor	unit	installed	rate	ISO
Hz							
wind speed, 117.5 m, centre	MM6	MM6_H117d5_Ws_Q1_m	Thies First Class Advanced 4.3352.00.000	m/s	TNO	4	*
wind speed, 112.5 m, 140°	MM6	MM6_H112d5B140_Ws_Q1_m	Thies First Class Advanced 4.3352.00.000	m/s	TNO	4	*
wind speed, 81.4 m, 140°	MM6	MM6_H081d4B140_Ws_Q1_m	Thies First Class Advanced 4.3352.00.000	m/s	TNO	4	*
wind speed, 81.4 m, 320°	MM6	MM6_H081d4B320_Ws_Q1_m	Thies First Class Advanced 4.3352.00.000	m/s	TNO	4	*
wind speed, 41.9 m, 140°	MM6	MM6_H041d9B140_Ws_Q1_m	Thies First Class Advanced 4.3352.00.000	m/s	TNO	4	*
wind speed, 41.9 m, 320°	MM6	MM6_H041d9B320_Ws_Q1_m	Thies First Class Advanced 4.3352.00.000	m/s	TNO	4	*
wind direction, 112.5 m, 320°	MM6	MM6_H112d5B320_Wd_Q1_m	Thies First Class 4.3150.00.400	°	TNO	4	*
wind direction, 77.4 m, 320°	MM6	MM6_H077d4B320_Wd_Q1_m	Thies First Class 4.3150.00.400	°	TNO	4	*
wind direction, 37.9 m, 320°	MM6	MM6_H037d9B320_Wd_Q1_m	Thies First Class 4.3150.00.400	°	TNO	4	*
air temperature, 109 m	MM6	MM6_H109_Temp_Q1_m	Vaisala RHT probe HMP155D	°C	TNO	4	*
relative humidity, 109 m	MM6	MM6_H109_RH_Q1_m	Vaisala RHT probe HMP155D	%	TNO	4	*
air pressure, 109 m	MM6	MM6_H109_Pair_Q1_m	Vaisala digital barometer PTB210	hPa	TNO	4	*
precipitation, 40 m	MM6	MM6_H040_Prec_Q1_m	Thies precipitation sensor 5.4103.10.000	%	TNO	4	*
precipitation, distro, 36 m	MM6	MM6_H036_Prec_Disdro_Q1_m	Thies LPM 5.4110.00.300	%	TNO	4	*
wind speed, sonic u, 108.5 m, 140°	MM6	MM6_H108d5B140_S_U_Q5_m	Metek 3D ultrasonic anemometer	m/s	TNO	4	*
wind speed, sonic v, 108.5 m, 140°	MM6	MM6_H108d5B140_S_V_Q5_m	Metek 3D ultrasonic anemometer	m/s	TNO	4	*
wind speed, sonic w, 108.5 m, 140°	MM6	MM6_H108d5B140_S_W_Q5_m	Metek 3D ultrasonic anemometer	m/s	TNO	4	*

Table B.3: List of equipment used per signal

Signal	Sensor						Module				
short name	brand / type	ID	gain	offset†	cal. due date‡	inst. date	type	ID	gain	off-set	cal. due date
MM6_H117d5_Ws_Q1_m	Thies 4.3352.00.000	94025503	4.579e-2	2.375e-1	2024-06-21	2023-06-21	NI 9423	94011863	1.000	0.000	2026-12-11
MM6_H112d5B140_Ws_Q1_m	Thies 4.3352.00.000	94025512	4.588e-2	2.243e-1	2024-06-21	2023-06-21	NI 9423	94011863	1.000	0.000	2026-12-11
MM6_H081d4B140_Ws_Q1_m	Thies 4.3352.00.000	94025502	4.577e-2	2.330e-1	2024-06-21	2023-06-21	NI 9423	94011863	1.000	0.000	2026-12-11
MM6_H081d4B320_Ws_Q1_m	Thies 4.3352.00.000	94025517	4.579e-2	2.350e-1	2024-06-21	2023-06-21	NI 9423	94011863	1.000	0.000	2026-12-11
MM6_H041d9B140_Ws_Q1_m	Thies 4.3352.00.000	94025504	4.593e-2	2.172e-1	2024-06-21	2023-06-21	NI 9423	94011863	1.000	0.000	2026-12-11
MM6_H041d9B320_Ws_Q1_m	Thies 4.3352.00.000	94025506	4.572e-2	2.376e-1	2024-06-21	2023-06-21	NI 9423	94011863	1.000	0.000	2026-12-11
MM6_H112d5B320_Wd_Q1_m	Thies 4.3150.00.400	94012542	1.000e-1	2.528e+2	2024-06-21	2023-06-21	NI 9871	94012138	1.000	0.000	N/A
MM6_H077d4B320_Wd_Q1_m	Thies 4.3150.00.400	94012052	1.000e-1	-1.510e+1	2024-06-21	2023-06-21	NI 9871	94012138	1.000	0.000	N/A
MM6_H037d9d9B320_Wd_Q1_m	Thies 4.3150.00.400	94012461	1.000e-1	-3.162e+2	2024-06-21	2023-06-21	NI 9871	94012138	1.000	0.000	N/A
MM6_H109_Temp_Q1_m	Vaisala HMP155	94012136	1.000e-2	0.000	2024-06-21	2023-06-21	NI 9871	94012165	1.000	0.000	N/A
MM6_H109_RH_Q1_m	Vaisala HMP155	94012136	1.000e-2	0.000	2024-06-21	2023-06-21	NI 9871	94012165	1.000	0.000	N/A
MM6_H109_Pair_Q1_m	Vaisala PTB210	94012651	1.000e-2	0.000	2024-06-21	2023-06-21	NI 9871	94012138	1.000	0.000	N/A
MM6_H040_Prec_Q1_m	Thies 5.4103.10.000	94012476	1.000	0.000	2024-06-21	2023-06-21	NI 9423	94011863	1.000	0.000	N/A
MM6_H036_Prec_Disdro_Q1_m	Thies 5.4110.00.300	94012652	1.000e-3	0.000	2024-10-14	2019-10-14	NI 9871	94012164	1.000	0.000	N/A
MM6_H108d5B140_WsUS_Q1_m	Metek 3D ultrasonic	94012039	1.000e-2	0.000	2023-11-28	2020-09-02	NI 9871	94012165	1.000	0.000	N/A
MM6_H108d5B140_WsVS_Q1_m	Metek 3D ultrasonic	94012039	1.000e-2	0.000	2023-11-28	2020-09-02	NI 9871	94012165	1.000	0.000	N/A
MM6_H108d5B140_WsWS_Q1_m	Metek 3D ultrasonic	94012039	1.000e-2	0.000	2023-11-28	2020-09-02	NI 9871	94012165	1.000	0.000	N/A

† For wind vanes the offset is governed by the North alignment of the vane w.r.t. its mounting orientation. Hence it does not reflect the offset reported on the calibration certificate.

‡ For cup anemometers and wind vanes the (annual) calibration due date is based on the installation date (not the wind tunnel calibration date). Note that the campaign end date exceeded the due date of the sonic anemometer. The sensor has been replaced on 27th Feb. 2024.

Table B.4: List of calculated (pseudo) signals

name	short name	unit	rate	ISO	constituents/derivation
Hz					
wind speed, 81.4 m	MM6_H081d4_Ws_True_Q1	m/s	4	*	MM6_H077d4B320_Wd_Q1 MM6_H081d4B140_Ws_MFDC_Q1_m B.1 MM6_H081d4B320_Ws_MFDC_Q1_m
wind speed, 41.9 m	MM6_H041d9_Ws_True_Q1	m/s	4	*	MM6_H037d9_Wd_Q1 MM6_H041d9B140_Ws_MFDC_Q1_m B.2 MM6_H041d9B320_Ws_MFDC_Q1_m
horizontal wind speed, sonic, 108.5 m	MM6_H108d5B140_WsHor_Q1	m/s	4	*	MM6_H108d5B140_WsUSon_Q1_m B.3 MM6_H108d5B140_WsVson_Q1_m

$$f(\#1, \#2, \#3) = \begin{cases} \#2, & \text{if } 50.45^\circ < \#1 \leq 230.45^\circ \\ \#3, & \text{otherwise} \end{cases} \quad (\text{B.1})$$

$$f(\#1, \#2, \#3) = \begin{cases} \#2, & \text{if } 49.84^\circ \leq \#1 < 229.84^\circ \\ \#3, & \text{otherwise} \end{cases} \quad (\text{B.2})$$

$$f(\#1, \#2) = \sqrt{\#1^2 + \#2^2} \quad (\text{B.3})$$

B.1.1 Cup anemometer



IECR and MEASNET approved test laboratory

Deutsche WindGuard Wind Tunnel Services GmbH

Member of / Mitglied im
Deutschen Kalibrierdienst

accredited to / akkreditiert nach
 DIN EN ISO/IEC 17025:2018

Object geprüft	Cup Anemometer
Manufacturer Hersteller	Thies Clima D-73083 Göttingen
Type Typ	4.3352.00.000
Serial number Fabrikations-Nr.	04201553
Customer Auftraggeber	TNO 2509 The Hague · The Netherlands
Order No. Auftragsnummer	3100333110
Project No. Projekt-Nr.	V7220163
Number of pages Anzahl der Seiten	5
Date of Calibration Datum der Kalibrierung	11.04.2022

This calibration certificate documents the traceability to national standards, which realize the units of measurement according to the International System of Units (SI). The DAkkS is signatory to the multilateral agreements of the European cooperation for Accreditation (EA) and of the International Laboratory Accreditation Cooperation (ILAC) for the mutual recognition of calibration certificates. The presented results relate only to the object calibrated at appropriate intervals. Dieser Kalibrierbescheinigung dokumentiert die Rückführung auf nationale Normale zur Darstellung der Einheit in Übereinstimmung mit dem internationalen Einheitensystem (SI). Der DAkkS ist unterzeichnender der multilateralen Übereinkommen der Europäischen Kooperation für Akkreditierung (EA) und der International Laboratory Accreditation Cooperation (ILAC) zur gegenseitigen Anerkennung der Kalibrierungen. Die dargestellten Ergebnisse beziehen sich nur auf den kalibrierten Gegenstand für die Einhaltung einer geeigneten Intervalle zur Wiederholung der Kalibrierung ist der Benutzer verantwortlich.

This calibration certificate may not be reproduced other than in full except with the permission of the issuing laboratory. Calibration certificates without signature are not valid. This calibration certificate has been generated electronically. Dieser Kalibrierbescheinigung darf nur vollständig und unverändert weiterverbreitet werden. Auszüge oder Änderungen bedürfen der Genehmigung des ausstellenden Kalibrierlaboratoriums. Kalibrierbescheinigung ohne Unterschrift haben keine Gültigkeit. Dieser Kalibrierbescheinigung wurde elektronisch erzeugt.

Date
Datum

13.04.2022

Prepared by / erstellt by: Approved by / genehmigt by:
Head of the calibration laboratory

H. Weber

Heiko Webermann, B. Sc.

Person in charge
Beauftragter

[Signature]

Manuel Spang, B. Eng.

Page 2 / 5
Seite

DkK
15140-01-00
04/2022

Calibration object Kalibriergegenstand	Cup Anemometer
Calibration procedure Kalibrierverfahren	IEC 61400-12-1:2017
Place of calibration Ort der Kalibrierung	Wind tunnel 1 of Deutsche WindGuard Wind Tunnel Services GmbH, Varel
Test conditions Messbedingungen	wind tunnel area 10000 cm ² DUT frontal area 230 cm ² diameter of mounting pipe 33,7 mm EN 10217 blockage ratio ¹⁾ 0,023 [-] software version P_9.1.0
Ambient conditions Umgebungsbedingungen	air temperature (22.4 ± 0.4) °C – (22.8 ± 0.4) °C air pressure (1015.4 ± 0.4) hPa – (1015.5 ± 0.4) hPa relative air humidity (84.7 ± 6.0) % – (85.5 ± 6.0) %
Measurement uncertainty Messunsicherheit	The expanded uncertainty assigned to the measurement results is obtained by multiplying the standard uncertainty by the coverage factor $k=2$. It has been determined in accordance with ISO 9010:2013. The value of the measured lies within the assigned range of values with a probability of 95%. The reference flow speed measurement is traceable to the German NM (Physikalisch-Technische Bundesanstalt) standard for flow speed. It is realized by using a PTF oven and calibrated Laser Doppler Anemometer (Expanded uncertainty 0.2 %, $n=2$)
Certificate ID Zertifikats-ID	9vc14agWwGzU2Xkx3j7b 
Additional remarks Zusätzliche Anmerkungen	Calibration after refurbishment
Revision Revision	0

¹⁾ Due to the special construction of the test section no blockage correction is necessary.

(b) Cup anemometer 94025503, page 2/4

Page 3 / 5 Seite	2211676		2211676						
	D-K:		D-K:						
	15140-01-00		15140-01-00						
	04/2022		04/2022						
Calibration result									
Kalibrierergebnis									
Reference	Combined	Test item							
Air velocity	Unc.	Output							
m/s	m/s	Hz							
3.947	0.050	81.397							
6.077	0.050	127.120							
8.100	0.051	171.573							
9.964	0.056	211.725							
11.924	0.067	255.523							
13.889	0.078	299.653							
15.942	0.089	342.713							
14.858	0.083	320.451							
12.885	0.073	276.824							
10.928	0.061	233.560							
8.987	0.051	190.740							
7.043	0.051	148.359							
5.040	0.050	105.394							
Graphical representation of the result									
Grafische Darstellung des Ergebnisses									
Calibration No: 2211676; 04201553; Calculated output at 10 m/s: 213.220 Hz Legend: * Reference Air velocity + Residuals									
Statistical analysis		Slope m	0.04579 (m/s)/(Hz) ±0.00006 (m/s)/(Hz)						
		Offset b	0.2375 m/s ±0.015 m/s						
		Standard error (Y) / RSD	0.0189 m/s						
		Correlation coefficient R	0.999989						
Remarks		The calibrated sensor complies with the demanded linearity of MEASNET							
Deutsche WindGuard Wind Tunnel Services GmbH		DEUTSCHE WINDGUARD		DEUTSCHE WINDGUARD					
Oldenburgstr. 65, D-26316 Varel		Oldenburgstr. 65, D-26316 Varel		Oldenburgstr. 65, D-26316 Varel					

(d) Cup anemometer 94025503, page 4/4

DEUTSCHE WINDGUARD
IECRE and MEASNET approved test laboratory

Calibration Certificate / Kalibrierschein
issued by the calibration laboratory / erstellt durch das Kalibrierlaboratorium

Deutsche WindGuard
Wind Tunnel Services GmbH

Member of / Mitglied im
Deutschen Kalibrierdienst

accredited to / akkreditiert nach
DIN EN ISO/IEC 17025:2018

Object
Gegenstand
Cup Anemometer

Manufacturer
Hersteller
Thies Clima
D-37083 Göttingen

Type
Typ
4.3352.00.000

Serial number
Fabrikat-Serien-Nr.
04201568
DEWS2724

Customer
Auftraggeber
TNO
2509 JE The Hague - The Netherlands

Order No.
Auftragsnummer
3100334634

Project No.
Projektnummer
VT220221

Number of pages
Anzahl der Seiten
5

Date of Calibration
Datum der Kalibrierung
21.04.2022

This calibration certificate documents the traceability to national standards, which realize the units of measurement according to the International System of Units (SI). The DAKKS is signatory to the multilateral agreements of the European co-operation for Accreditation (EA) and of the International Laboratory Accreditation Cooperation (ILAC) for the mutual recognition of calibration certificates. The presented results relate only to the calibrated object. The user is obliged to have the object recalibrated at appropriate intervals. Dieser Kalibrierschein dokumentiert die Rückführung auf nationale Normale zur Darstellung der Einheiten in Übereinstimmung mit dem internationalen Einheitensystem (SI). Die DAKKS ist Unterzeichner der multilateralen Übereinkommen der Europäischen Zusammenarbeit für Akkreditierung (EA) und der Internationalen Laboratoriumsakkreditierung (ILAC) zur gegenseitigen Anerkennung der Kalibrierscheine. Die dargestellten Ergebnisse beziehen sich nur auf den kalibrierten Gegenstand. Für die Einhaltung einer angemessenen Frist zur Wiederholung der Kalibrierung ist der Benutzer verantwortlich.

This calibration certificate may not be reproduced other than in full except with the permission of the issuing laboratory. Calibration certificates without signature are not valid. This calibration certificate has been generated electronically. Dieser Kalibrierschein darf nur vollständig und unverändert weiterverbreitet werden. Auszüge oder Änderungen bedürfen der Genehmigung des ausstellenden Kalibrierlaboratoriums. Kalibrierscheine ohne Unterschrift haben keine Gültigkeit. Dieser Kalibrierschein wurde elektronisch erzeugt.

Date
Datum
21.04.2022

Prepared by / Approved by
Head of the calibration laboratory
Hilke Westermann, B. Sc.

Person in charge
Responsible
Tobias Andre Krummen

Page 2 / 5
Seite

Calibration object
Kalibriergegenstand
Cup Anemometer

Calibration procedure
Kalibrierverfahren
IEC 61400-12-3:2017

Place of calibration
Ort der Kalibrierung
Wind tunnel 2 of Deutsche WindGuard Wind Tunnel Services GmbH, Varel

Test conditions
Messbedingungen
wind tunnel area 10000 cm²
DUT frontal area 230 cm²
diameter of mounting pipe 33.7 mm EN 10217
blockage ratio ¹⁾ 0.028 [-]
software version P_9.1.0
¹⁾ Due to the special construction of the test section no blockage correction is necessary.

Ambient conditions
Umgebungsbedingungen
air temperature (21.5 ± 0.4) °C – (21.8 ± 0.4) °C
air pressure (1016.1 ± 0.4) hPa – (1016.1 ± 0.4) hPa
relative air humidity (32.0 ± 6.0) % – (32.2 ± 6.0) %

Measurement uncertainty
Messunsicherheit
The expanded uncertainty assigned to the measurement results is obtained by multiplying the standard uncertainty by the coverage factor $k=2$. It has been determined in accordance with EA-4/02: M: 2013. The value of the measured lies within the assigned range of values with a probability of 95%. The reference flow speed measurement is traceable to the German 1001 (Physikalisch-Technische Bundesanstalt) standard for flow speed. It is realized by using a PTB owned and calibrated Laser Doppler Anemometer (Expanded uncertainty 0.2 %, $k=2$)

Certificate ID
Zertifikat-ID
NdF5tgh5BfwLbldVd5v8B5

Additional remarks
Zusätzliche Anmerkungen
Calibration after refurbishment

Revision
Revision
0

(e) Cup anemometer 94025512, page 1/4

Page 3 / 5
Seite

Calibration result
Kalibrierergebnis

Reference	Combined	Test item
Air velocity	Unc.	Output
m/s	m/s	Hz
3.972	0.040	82.089
6.070	0.040	127.430
8.030	0.041	170.443
10.385	0.041	214.488
12.064	0.048	257.818
14.067	0.057	302.769
16.109	0.065	347.686
15.076	0.061	322.970
13.044	0.053	278.821
11.064	0.045	235.384
9.032	0.041	192.224
6.986	0.040	147.116
4.999	0.040	104.060

Deutsche WindGuard Wind Tunnel Services GmbH
Oldenburgstr. 65, D-26316 Varel

DEUTSCHE WINDGUARD

(g) Cup anemometer 94025512, page 3/4

(f) Cup anemometer 94025512, page 2/4

Page 4 / 5
Seite

Graphical representation of the result
Grafische Darstellung des Ergebnisses

Calibration No: 2221388; 04201568; DEWS2724

Statistical analysis

Slope m	0.04588 (m/s)/Hz ± 0.00010 (m/s)/Hz
Offset b	0.2243 m/s ± 0.022 m/s
Standard error (Y) / RSD	0.0285 m/s
Correlation coefficient R	0.999976

Remarks
The calibrated sensor complies with the demanded linearity of MEASNET

Deutsche WindGuard Wind Tunnel Services GmbH
Oldenburgstr. 65, D-26316 Varel

DEUTSCHE WINDGUARD

(h) Cup anemometer 94025512, page 4/4

DEUTSCHE
WINDGUARD

IECRE and MEASNET approved test laboratory

Calibration Certificate / Kalibrierschein
issued by the calibration laboratory / erstellt durch das Kalibrierlaboratorium

Deutsche WindGuard
Wind Tunnel Services GmbH

Member of / Mitglied im
Deutschen Kalibrierdienst

accredited to / akkreditiert nach
DIN EN ISO/IEC 17025:2018

Object
Gegenstand Cup Anemometer

Manufacturer
Hersteller Thies Clima
D-37083 Göttingen

Type
Typ 4.3352.00.000

Serial number
Fabrikat/ Serien-Nr. 04201552

Customer
Auftraggeber TNO
2302 JE The Hague - The Netherlands

Order No.
Auftragsnummer Email 2022-06-24_Danzl

Project No.
Projektnummer VT220621

Number of pages
Anzahl der Seiten 5

Date of Calibration
Datum der Kalibrierung 06.07.2022

This calibration certificate documents the traceability to national standards, which realize the units of measurement according to the International System of Units (SI). The DAKKS is signatory to the multilateral agreements of the European co-operation for Accreditation (EA) and of the International Laboratory Accreditation Cooperation (ILAC) for the mutual recognition of calibration certificates. The presented results relate only to the calibrated object. The user is obliged to have the object recalibrated at appropriate intervals. Dieser Kalibrierschein dokumentiert die Rückführung auf nationale Normale zur Darstellung der Einheiten in Übereinstimmung mit dem internationalen Einheitensystem (SI). Die DAKKS ist Unterzeichner der multilateralen Übereinkommen der European co-operation for Accreditation (EA) und der International Laboratory Accreditation Cooperation (ILAC) zur gegenseitigen Anerkennung der Kalibrierscheine. Die dargestellten Ergebnisse beziehen sich nur auf den kalibrierten Gegenstand. Für die Einhaltung einer angemessenen Frist zur Wiederholung der Kalibrierung ist der Benutzer verantwortlich.

This calibration certificate may not be reproduced other than in full except with the permission of the issuing laboratory. Calibration certificates without signature are not valid. This calibration certificate has been generated electronically. Dieser Kalibrierschein darf nur vollständig und unverändert weiterverbreitet werden. Auszüge oder Änderungen bedürfen der Genehmigung des ausstellenden Kalibrierlaboratoriums. Kalibrierscheine ohne Unterschrift haben keine Gültigkeit. Dieser Kalibrierschein wurde elektronisch erzeugt.

Date
Datum 06.07.2022

Prepared by / Approved by
head of the calibration laboratory
Hilke Westermann, B. Sc.

Person in charge
Beauftragter
R. Rinkel
Techniker Robert Rinkel

Page 2 / 5
Seite

2222333
D-K
15140-01-00
07/2022

Calibration object
Kalibriergegenstand Cup Anemometer

Calibration procedure
Kalibrierverfahren IEC 61400-12-3:2017

Place of calibration
Ort der Kalibrierung Wind tunnel 2 of Deutsche WindGuard Wind Tunnel Services GmbH, Varel

Test conditions
Messbedingungen

wind tunnel area 10000 cm²
DUT frontal area 230 cm²
diameter of mounting pipe 33.7 mm EN 10217
blockage ratio ¹⁾ 0.028 [-]
software version P_9.1.0_CAN_NI
¹⁾ Due to the special construction of the test section no blockage correction is necessary.

Ambient conditions
Umgebungsbedingungen

air temperature (24.9 ± 0.4) °C
air pressure (1022.9 ± 0.4) hPa – (1023.1 ± 0.4) hPa
relative air humidity (39.7 ± 6.0) % – (40.2 ± 6.0) %

Measurement uncertainty
Messunsicherheit

The expanded uncertainty assigned to the measurement results is obtained by multiplying the standard uncertainty by the coverage factor $k=2$. It has been determined in accordance with EA-4/02: M: 2013. The value of the measured lies within the assigned range of values with a probability of 95%. The reference flow speed measurement is traceable to the German 1001 (Physikalisch-Technische Bundesanstalt) standard for flow speed. It is realized by using a PTB owned and calibrated Laser Doppler Anemometer (Expanded uncertainty 0.2 %, $k=2$)

Certificate ID
Zertifikat-ID ChurpTnWt8dvPPyPT37x

Additional remarks
Zusätzliche Anmerkungen Calibration before refurbishment

Revision
Revision 0

(i) Cup anemometer 94025502, page 1/4

Page 3 / 5
Seite

2222333
D-K
15140-01-00
07/2022

Calibration result
Kalibrierergebnis

Reference	Combined	Test item
Air velocity	Unc	Output
m/s	m/s	Hz
3.866	0.040	79.751
6.037	0.041	127.235
8.047	0.041	171.761
10.234	0.041	214.780
12.038	0.040	258.617
14.075	0.037	302.832
16.050	0.036	346.755
15.069	0.041	324.015
13.037	0.044	260.184
11.044	0.046	226.389
9.035	0.041	182.629
6.975	0.041	147.029
4.976	0.040	100.341

Deutsche WindGuard Wind Tunnel Services GmbH
Oldenburgerstr. 65, D-26316 Varel

DEUTSCHE
WINDGUARD

(k) Cup anemometer 94025502, page 3/4

(j) Cup anemometer 94025502, page 2/4

Page 4 / 5
Seite

2222333
D-K
15140-01-00
07/2022

Graphical representation of the result
Grafische Darstellung des Ergebnisses

Calibration No: 2222333; 04201552;

Statistical analysis

Slope m 0.04566 (m/s)/Hz ± 0.00007 (m/s)/Hz
Offset b 0.2321 m/s ± 0.016 m/s
Standard error (Y) / RSD 0.0202 m/s
Correlation coefficient R 0.99988

Remarks
The calibrated sensor complies with the demanded linearity of MEASNET

Deutsche WindGuard Wind Tunnel Services GmbH
Oldenburgerstr. 65, D-26316 Varel

DEUTSCHE
WINDGUARD

(l) Cup anemometer 94025502, page 4/4

DEUTSCHE
WINDGUARD

IECRE and MEASNET approved test laboratory

Calibration Certificate / Kalibrierschein
issued by the calibration laboratory / erstellt durch das Kalibrierlaboratorium

Deutsche WindGuard
Wind Tunnel Services GmbH

Member of / Mitglied im
Deutschen Kalibrierdienst

accredited to / akkreditiert nach
DIN EN ISO/IEC 17025:2018

Object
Gegenstand Cup Anemometer

Manufacturer
Hersteller Thies Clima
D-37083 Göttingen

Type
Typ 4.3352.00.000

Serial number
Fabrikat/Serien-Nr. 04201564

Customer
Auftraggeber TNO
2302 JE The Hague - The Netherlands

Order No.
Auftragsnummer 3100334634

Project No.
Projektnummer VT220221

Number of pages
Anzahl der Seiten 5

Date of Calibration
Datum der Eichleistung 21.04.2022

This calibration certificate documents the traceability to national standards, which realize the units of measurement according to the International System of Units (SI). The DAKKS is signatory to the multilateral agreements of the European co-operation for Accreditation (EA) and of the International Laboratory Accreditation Cooperation (ILAC) for the mutual recognition of calibration certificates. The presented results relate only to the calibrated object. The user is obliged to have the object recalibrated at appropriate intervals. Dieser Kalibrierschein dokumentiert die Rückführung auf nationale Normale zur Darstellung der Einheiten in Übereinstimmung mit dem internationalen Einheitensystem (SI). Die DAKKS ist Unterzeichner der multilateralen Übereinkommen der Europäischen Zusammenarbeit für Akkreditierung (EA) und der Internationalen Laboratoriums-Akkreditierungszusammenarbeit (ILAC) zur gegenseitigen Anerkennung der Kalibrierscheine. Die dargestellten Ergebnisse beziehen sich nur auf den kalibrierten Gegenstand. Für die Einhaltung einer angemessenen Frist zur Wiederholung der Kalibrierung ist der Benutzer verantwortlich.

This calibration certificate may not be reproduced other than in full except with the permission of the issuing laboratory. Calibration certificates without signature are not valid. This calibration certificate has been generated electronically. Dieser Kalibrierschein darf nur vollständig und unverändert weiterverbreitet werden. Auszüge oder Änderungen bedürfen der Genehmigung des ausstellenden Kalibrierlaboratoriums. Kalibrierscheine ohne Unterschrift haben keine Gültigkeit. Dieser Kalibrierschein wurde elektronisch erzeugt.

Date
Datum 21.04.2022

Freigegeben durch / Approved by
Head of the calibration laboratory
Hilke Westermann, B. Sc.

Person in charge
Responsible
Tobias Andre Krummen

Page 2 / 5
Seite

2221387
D-4-
15140-01-00
04/2022

Calibration object
Kalibriergegenstand Cup Anemometer

Calibration procedure
Kalibrierverfahren IEC 61400-12-3:2017

Place of calibration
Ort der Kalibrierung Wind tunnel 2 of Deutsche WindGuard Wind Tunnel Services GmbH, Varel

Test conditions
Messbedingungen

wind tunnel area 10000 cm²
DUT frontal area 230 cm²
diameter of mounting pipe 33.7 mm EN 10217
blockage ratio ¹⁾ 0.028 [-]
software version P_9.1.0
¹⁾ Due to the special construction of the test section no blockage correction is necessary.

Ambient conditions
Umgebungsbedingungen

air temperature (21.4 ± 0.4) °C – (21.7 ± 0.4) °C
air pressure (1016.1 ± 0.4) hPa – (1016.2 ± 0.4) hPa
relative air humidity (32.0 ± 6.0) % – (32.3 ± 6.0) %

Measurement uncertainty
Messunsicherheit

The expanded uncertainty assigned to the measurement results is obtained by multiplying the standard uncertainty by the coverage factor $k=2$. It has been determined in accordance with EA-4/02: M: 2013. The value of the measured lies within the assigned range of values with a probability of 95%. The reference flow speed measurement is traceable to the German 1001 (Physikalisch-Technische Bundesanstalt) standard for flow speed. It is realized by using a PTB owned and calibrated Laser Doppler Anemometer (Expanded uncertainty 0.2 %, $k=2$)

Certificate ID
Zertifikat-ID HVtktptuunJMSHMEZngWt

Additional remarks
Zusätzliche Anmerkungen Calibration after refurbishment

Revision
Revision 0

Deutsche WindGuard Wind Tunnel Services GmbH
Oldenburgerstr. 65, D-26316 Varel

DEUTSCHE
WINDGUARD

(m) Cup anemometer 94025517, page 1/4

Page 3 / 5
Seite

2221387
D-4-
15140-01-00
04/2022

Calibration result
Kalibrierergebnis

Reference Air velocity m/s	Combined Output m/s	Test Item Output Hz
3.983	0.040	81.731
6.070	0.040	127.201
8.079	0.040	171.076
10.076	0.041	214.984
12.070	0.040	258.484
14.115	0.037	302.722
16.062	0.065	346.441
15.075	0.061	324.077
13.090	0.063	280.429
11.060	0.040	230.957
9.043	0.040	192.270
6.987	0.040	147.858
4.993	0.040	104.444

Deutsche WindGuard Wind Tunnel Services GmbH
Oldenburgerstr. 65, D-26316 Varel

DEUTSCHE
WINDGUARD

(o) Cup anemometer 94025517, page 3/4

(n) Cup anemometer 94025517, page 2/4

Page 4 / 5
Seite

2221387
D-4-
15140-01-00
04/2022

Graphical representation of the result
Graphische Darstellung des Ergebnisses

Calibration No: 2221387, 04201564;

Statistical analysis

Slope m 0.04579 (m/s)/Hz ± 0.00006 (m/s)/Hz
Offset b 0.2350 m/s ± 0.024 m/s
Standard error (Y) / RSD 0.0178 m/s
Correlation coefficient R 0.999991

Remarks
The calibrated sensor complies with the demanded linearity of MEASNET

Deutsche WindGuard Wind Tunnel Services GmbH
Oldenburgerstr. 65, D-26316 Varel

DEUTSCHE
WINDGUARD

(p) Cup anemometer 94025517, page 4/4

DEUTSCHE
WINDGUARD

IECRE and MEASNET approved test laboratory

Calibration Certificate / Kalibrierschein
issued by the calibration laboratory / erstellt durch das Kalibrierlaboratorium

Deutsche WindGuard
Wind Tunnel Services GmbH

Member of / Mitglied im
Deutschen Kalibrierdienst

accredited to / akkreditiert nach
DIN EN ISO/IEC 17025:2018

Object
Gegenstand Cup Anemometer

Manufacturer
Hersteller Thies Clima
D-37083 Göttingen

Type
Typ 4.3352.00.000

Serial number
Fabrikat/Serien-Nr. 04201560

Customer
Auftraggeber TNO
2302 JE The Hague - The Netherlands

Order No.
Auftragsnummer 3100333110

Project No.
Projektnummer VT220163

Number of pages
Anzahl der Seiten 5

Date of Calibration
Datum der Kalibrierung 13.04.2022

This calibration certificate documents the traceability to national standards, which realize the units of measurement according to the International System of Units (SI). The DAKKS is signatory to the multilateral agreements of the European co-operation for Accreditation (EA) and of the International Laboratory Accreditation Cooperation (ILAC) for the mutual recognition of calibration certificates. The presented results relate only to the calibrated object. The user is obliged to have the object recalibrated at appropriate intervals. Dieser Kalibrierschein dokumentiert die Rückführung auf nationale Normale zur Darstellung der Einheit in Übereinstimmung mit dem internationalen Einheitensystem (SI). Die DAKKS ist Unterzeichner der multilateralen Übereinkommen der Europäischen Zusammenarbeit für Akkreditierung (EA) und der Internationalen Laboratoriumszusammenarbeit (ILAC) zur gegenseitigen Anerkennung der Kalibrierscheine. Die dargestellten Ergebnisse beziehen sich nur auf den kalibrierten Gegenstand. Für die Einhaltung einer angemessenen Frist zur Wiederholung der Kalibrierung ist der Benutzer verantwortlich.

This calibration certificate may not be reproduced other than in full except with the permission of the issuing laboratory. Calibration certificates without signature are not valid. This calibration certificate has been generated electronically. Dieser Kalibrierschein darf nur vollständig und unverändert weiterverbreitet werden. Auszüge oder Änderungen bedürfen der Genehmigung des ausstellenden Kalibrierlaboratoriums. Kalibrierscheine ohne Unterschrift haben keine Gültigkeit. Dieser Kalibrierschein wurde elektronisch erzeugt.

Date
Datum 13.04.2022

Prepared by / Approved by
head of the calibration laboratory
Hilke Westermann, B. Sc.

Person in charge
Beauftragter
Manfred Böhling, B. Eng.

Page 2 / 5
Seite

2211679
D-4-
15140-01-00
04/2022

Calibration object
Kalibriergegenstand Cup Anemometer

Calibration procedure
Kalibrierverfahren IEC 61400-12-3:2017

Place of calibration
Ort der Kalibrierung Wind tunnel 1 of Deutsche WindGuard Wind Tunnel Services GmbH, Varel

Test conditions
Messbedingungen

wind tunnel area 10000 cm²
DUT frontal area 230 cm²
diameter of mounting pipe 33.7 mm EN 10217
blockage ratio ¹⁾ 0.023 [-]
software version P_9.1.0
¹⁾ Due to the special construction of the test section no blockage correction is necessary.

Ambient conditions
Umgebungsbedingungen

air temperature (22.8 ± 0.4) °C – (23.2 ± 0.4) °C
air pressure (1015.8 ± 0.4) hPa – (1015.8 ± 0.4) hPa
relative air humidity (34.7 ± 6.0) % – (35.3 ± 6.0) %

Measurement uncertainty
Messunsicherheit

The expanded uncertainty assigned to the measurement results is obtained by multiplying the standard uncertainty by the coverage factor $k=2$. It has been determined in accordance with EA-4/02: M: 2013. The value of the measured lies within the assigned range of values with a probability of 95%. The reference flow speed measurement is traceable to the German 1001 (Physikalisch-Technische Bundesanstalt) standard for flow speed. It is realized by using a PTB owned and calibrated Laser Doppler Anemometer (Expanded uncertainty 0.2 %, $k=2$).

Certificate ID
Zertifikat-ID X8gRnu2ELm5b6498ZC

Additional remarks
Zusätzliche Anmerkungen Calibration after refurbishment

Revision
Revision 0

(q) Cup anemometer 94025504, page 1/4

Page 3 / 5
Seite

2211679
D-4-
15140-01-00
04/2022

Calibration result
Kalibrierergebnis

Reference Air velocity m/s	Combined Output m/s	Test Item Output Hz
3.944	0.050	81.081
6.075	0.051	127.441
8.102	0.051	171.831
9.859	0.046	212.429
11.922	0.067	254.856
13.875	0.077	296.753
15.925	0.089	342.096
14.895	0.083	318.890
12.875	0.072	275.462
10.168	0.061	213.254
8.363	0.051	190.219
7.044	0.050	148.791
5.054	0.050	105.179

Deutsche WindGuard Wind Tunnel Services GmbH
Oldenburgerstr. 65, D-26316 Varel

DEUTSCHE
WINDGUARD

(s) Cup anemometer 94025504, page 3/4

(r) Cup anemometer 94025504, page 2/4

Page 4 / 5
Seite

2211679
D-4-
15140-01-00
04/2022

Graphical representation of the result
Grafische Darstellung des Ergebnisses

Calibration No: 2211679; 04201560;

Reference Air velocity / m/s

Test Item Output / Hz

Calculated output at 10 m/s: 212.970 Hz

Reference Air velocity

Residuals

Statistical analysis

Slope m 0.04593 (m/s)/Hz ± 0.00004 (m/s)/Hz
Offset b 0.2172 m/s ± 0.010 m/s
Standard error (Y) / RSD 0.0123 m/s
Correlation coefficient R 0.999995

Remarks

The calibrated sensor complies with the demanded linearity of MEASNET

Deutsche WindGuard Wind Tunnel Services GmbH
Oldenburgerstr. 65, D-26316 Varel

DEUTSCHE
WINDGUARD

(t) Cup anemometer 94025504, page 4/4

Page 2 / 5 Seite	27138171 D-6-15046-06-06 09/2022
Calibration object <i>Kalibriergegenstand</i>	Cup Anemometer
Calibration procedure <i>Kalibrierverfahren</i>	IEC 61400-12-1:2017
Place of calibration <i>Ort der Kalibrierung</i>	Wind tunnel 1 of German WindGuard Wind Tunnel Services GmbH, Varel
Test conditions <i>Messbedingungen</i>	wind tunnel area 10000 cm² DUT frontal area 230 cm² diameter of mounting pipe 33.7 mm EN 10217 blockage ratio ¹⁾ 0.023 [] software version P_8.10_0AN_NI
¹⁾ Due to the special construction of the test section no blockage correction is necessary.	
Ambient conditions <i>Umgebungsbedingungen</i>	air temperature (23.7 ± 0.4) °C – (24.0 ± 0.4) °C
Measurement uncertainty <i>Messunsicherheit</i>	air pressure (1012.3 ± 0.4) hPa – (1012.4 ± 0.4) hPa
	relative air humidity (47.5 ± 6.0) % – (48.4 ± 6.0) %
The expanded uncertainty assigned to the measurement results is obtained by multiplying the standard uncertainty by the coverage factor $k=2$. It has been determined in accordance with EA-402 M: 2013. The value of the measurement lies within the assigned range of values with a probability of 95%. The reference flow speed measurement is traceable to the German NMJ (Physikalisch-Technische Bundesanstalt) standard for flow speed. It is realized by using a P7B oriented and calibrated Laser Doppler Anemometer (Expanded uncertainty 0.2 %, $k=2$)	
Certificate ID <i>Zertifikat ID</i>	JGQZdyCZyqkTPGhtMxI 
Additional remarks <i>Zusätzliche Bemerkungen</i>	Calibration after refurbishment
Revision <i>Revision</i>	0

(v) Cup anemometer 94025506, page 2/4

Page 4 / 5
Seite

Graphical representation of the result
Grafische Darstellung des Ergebnisses

Calibration No: 2213871; 04201556; DEWS2718

Calculated output at 10 min: 215.650 Hz

Test Item Output / Hz	Reference Air velocity / m/s	Residuals / m/s
100	4.5	11.5
110	5.5	10.5
120	6.5	9.5
130	7.5	8.5
140	8.5	7.5
150	9.5	6.5
160	10.5	5.5
170	11.5	4.5
180	12.5	3.5
190	13.5	2.5
200	14.5	1.5
210	15.5	0.5
220	16.5	-0.5
230	17.5	-1.5
240	18.5	-2.5
250	19.5	-3.5
260	20.5	-4.5
270	21.5	-5.5
280	22.5	-6.5
290	23.5	-7.5
300	24.5	-8.5
310	25.5	-9.5
320	26.5	-10.5
330	27.5	-11.5
340	28.5	-12.5
350	29.5	-13.5
360	30.5	-14.5
370	31.5	-15.5
380	32.5	-16.5
390	33.5	-17.5
400	34.5	-18.5

Statistical analysis

Parameter	Value
Slope m	0.04572 (m/s)/(Hz) ± 0.00005 (m/s)/(Hz)
Offset b	0.2376 m/s ± 0.011 m/s
Standard error (Y) / RSD	0.0138 m/s
Correlation coefficient R	0.999994

Remarks

The calibrated sensor complies with the demanded linearity of MEASNET

Deutsche WindGuard Wind Tunnel Services GmbH
Görlitzerstrasse 46 • D-10116 Berlin

BRUNNEN
WINDGUARD

(x) Cup anemometer 94025506, page 4/4

B.1.2 Wind vane

DEUTSCHE WINDGUARD
IECR and MEASNET approved test laboratory

Calibration Certificate / Kalibrierschein
issued by the calibration laboratory / erstellt durch das Kalibrierlaboratorium

Deutsche WindGuard Wind Tunnel Services GmbH

Member of / Mitglied im
Deutschen Kalibrierdienst

accredited to / akkreditiert nach
DIN EN ISO/IEC 17025:2018

Object
Wind Vane

Manufacturer
Thies Clima
D-37083 Göttingen

Type
4.3150.00.400

Serial number
04120058

Customer
TNO
2509 JE The Hague - The Netherlands

Order No.
3100333110

Project No.
VT220163

Number of pages
6

Date of Calibration
07.04.2022

This calibration certificate documents the traceability to national standards, which realize the units of measurement according to the International System of Units (SI). The DAkkS is signatory to the multilateral agreements of the European co-operation for Accreditation (EA) and of the International Laboratory Accreditation Cooperation (ILAC) for the mutual recognition of calibration certificates. The presented results relate only to the calibrated object. The user is obliged to have the object recalibrated at appropriate intervals. Dieser Kalibrierschein dokumentiert die Rückführung auf nationale Normale zur Darstellung der Einheit in Übereinstimmung mit dem internationalen Einheitensystem (SI). Die DAkkS ist Unterzeichner der multilateralen Übereinkommen der Europäischen Kooperation für Akkreditierung (EA) und der Internationalen Laboratoriums-Akkreditierung-Organisation (ILAC) zur gegenseitigen Anerkennung der Kalibrierscheine. Die dargestellten Ergebnisse beziehen sich nur auf den kalibrierten Gegenstand. Für die Einhaltung einer angemessenen Frist zur Wiederholung der Kalibrierung ist der Benutzer verantwortlich.

This calibration certificate may not be reproduced other than in full except with the permission of the issuing laboratory. Calibration certificates without signature are not valid. This calibration certificate has been generated electronically. Dieser Kalibrierschein darf nur vollständig und unverändert weiterverbreitet werden. Auszüge oder Änderungen bedürfen der Genehmigung des ausstellenden Kalibrierlaboratoriums. Kalibrierscheine ohne Unterschrift haben keine Gültigkeit. Dieser Kalibrierschein wurde elektronisch erzeugt.

Date / Datum: 07.04.2022
Person in charge / Approved by / Verantwortlich: *[Signature]*
Person in charge / Approved by / Verantwortlich: *[Signature]*
Tobias Schmidt, B. Sc.

(a) Wind vane 94012542, page 1/6

Page 3 / 6
Seite

2211573
D-K:
15140-01-00
04/2022

Calibration result (1/3)
Kalibrierergebnis (1/3)

Reference	Reference	Reference	Reference	Combined	Test item	Test item
Air velocity	Unc	Yaw angle	Unc	Direction	Deviation	Deviation
m/s	m/s	deg	deg	deg	deg	deg
7.88	0.04	0.01	0.80	1.11	4.52	-0.49
7.87	0.04	10.00	0.80	1.11	0.41	-0.60
7.88	0.04	15.01	0.80	1.11	14.38	-0.63
7.88	0.04	20.01	0.80	1.11	18.33	-0.69
7.88	0.04	25.01	0.80	1.11	24.36	-0.65
7.88	0.04	30.00	0.80	1.11	29.41	-0.59
7.88	0.04	35.01	0.80	1.11	34.45	-0.56
7.88	0.04	39.67	0.80	1.11	39.38	-0.49
7.88	0.04	44.99	0.80	1.11	44.57	-0.42
7.88	0.04	50.00	0.80	1.11	49.60	-0.40
7.88	0.04	55.01	0.80	1.11	54.67	-0.34
7.88	0.04	59.99	0.80	1.11	59.60	-0.33
7.89	0.04	64.99	0.80	1.11	64.65	-0.34
7.89	0.04	70.00	0.80	1.11	69.64	-0.36
7.88	0.04	75.00	0.80	1.11	74.60	-0.40
7.89	0.04	80.00	0.80	1.11	79.53	-0.47
7.88	0.04	85.00	0.80	1.11	84.48	-0.52
7.88	0.04	90.00	0.80	1.11	89.40	-0.60
7.88	0.04	95.00	0.80	1.11	94.28	-0.71
7.88	0.04	100.00	0.80	1.11	99.21	-0.79
7.88	0.04	105.00	0.80	1.11	104.19	-0.81
7.88	0.04	110.00	0.80	1.11	109.20	-0.80
7.89	0.04	115.00	0.80	1.11	114.27	-0.71
7.88	0.04	120.00	0.80	1.11	119.29	-0.71
7.88	0.04	124.99	0.80	1.11	124.32	-0.68
7.88	0.04	129.99	0.80	1.11	129.39	-0.61
7.88	0.04	135.00	0.80	1.11	134.48	-0.52
7.89	0.04	140.00	0.80	1.11	139.54	-0.46
7.88	0.04	145.00	0.80	1.11	144.55	-0.45
7.88	0.04	150.00	0.80	1.11	149.59	-0.40
7.88	0.04	154.99	0.80	1.11	154.64	-0.35

(c) Wind vane 94012542, page 3/6

Page 2 / 6
Seite

2211573
D-K:
15140-01-00
04/2022

Calibration object
Kalibriergegenstand: Wind Vane

Calibration procedure
Kalibrierverfahren: IEC 61400-12-1:2017

Place of calibration
Ort der Kalibrierung: Wind tunnel 1 of Deutsche WindGuard Wind Tunnel Services GmbH, Varel

Test conditions
Messbedingungen:

wind tunnel area	10000 cm ²
DUT frontal area	200 cm ²
diameter of mounting pipe	33.7 mm
blockage ratio ¹⁾	0.020 []
software version	P. 9.1.0

¹⁾ Due to the special construction of the test section no blockage correction is necessary.

Ambient conditions
Umgebungsbedingungen:

air temperature	(19.7 ± 0.4) °C – (20.2 ± 0.4) °C
air pressure	(976.6 ± 0.4) hPa – (977.9 ± 0.4) hPa
relative air humidity	(59.0 ± 6.0) % – (59.7 ± 6.0) %

Measurement uncertainty
Messunsicherheit: The expanded uncertainty assigned to the measurement results is obtained by multiplying the standard uncertainty by the coverage factor k=2. It has been determined in accordance with EA-4/02:2013. The value of the measurand lies within the assigned range of values with a probability of 95%. The reference flow speed measurement is traceable to the German NMJ (Physikalisch-Technische Bundesanstalt) standard for flow speed. It is realized by using a P18 owned and calibrated Laser Doppler Anemometer [Expanded uncertainty 0.2 %, k=2]

Additional remarks
Zusätzliche Anmerkungen: North alignment via north mark

Revision
Revision: 0

Deutsche WindGuard Wind Tunnel Services GmbH
Oldenburgerstr. 65, D-26316 Varel

DEUTSCHE WINDGUARD

(b) Wind vane 94012542, page 2/6


Page 4 / 6
Seite

2211573
D-K:
15140-01-00
04/2022

Calibration result (2/3)
Kalibrierergebnis (2/3)

Reference	Reference	Reference	Reference	Combined	Test item	Test item
Air velocity	Unc	Yaw angle	Unc	Direction	Deviation	Deviation
m/s	m/s	deg	deg	deg	deg	deg
7.88	0.04	155.99	0.80	1.11	155.85	-0.20
7.88	0.04	164.99	0.80	1.11	164.62	-0.38
7.88	0.04	169.99	0.80	1.11	169.53	-0.46
7.88	0.04	175.00	0.80	1.11	174.47	-0.53
7.88	0.04	180.00	0.80	1.11	179.37	-0.63
7.88	0.04	185.00	0.80	1.11	184.32	-0.68
7.88	0.04	190.01	0.80	1.11	189.29	-0.72
7.88	0.04	195.00	0.80	1.11	194.28	-0.72
7.88	0.04	200.00	0.80	1.11	199.29	-0.71
7.88	0.04	205.00	0.80	1.11	204.34	-0.66
7.88	0.04	209.98	0.80	1.11	209.39	-0.60
7.88	0.04	214.99	0.80	1.11	214.46	-0.53
7.88	0.04	220.00	0.80	1.11	219.57	-0.43
7.88	0.04	224.99	0.80	1.11	224.69	-0.30
7.88	0.04	229.99	0.80	1.11	229.76	-0.23
7.89	0.04	235.00	0.80	1.11	234.83	-0.17
7.88	0.04	240.00	0.80	1.11	239.86	-0.14
7.88	0.04	244.99	0.80	1.11	244.81	-0.17
7.88	0.04	249.98	0.80	1.11	249.83	-0.15
7.88	0.04	255.01	0.80	1.11	254.79	-0.21
7.88	0.04	259.99	0.80	1.11	259.73	-0.27
7.88	0.04	264.99	0.80	1.11	264.70	-0.29
7.88	0.04	270.01	0.80	1.11	269.63	-0.39
7.88	0.04	274.99	0.80	1.11	274.52	-0.47
7.88	0.04	279.99	0.80	1.11	279.52	-0.47
7.88	0.04	285.01	0.80	1.11	284.49	-0.52
7.88	0.04	290.01	0.80	1.11	289.49	-0.52
7.88	0.04	295.01	0.80	1.11	294.54	-0.47
7.88	0.04	300.01	0.80	1.11	299.57	-0.44
7.88	0.04	305.00	0.80	1.11	304.65	-0.35
7.88	0.04	309.99	0.80	1.11	309.70	-0.29

(d) Wind vane 94012542, page 4/6




Page 2 / 6 Seite	2221179 04-1546-04-06 04/2022
Calibration object Kalibriergegenstand	Wind Vane
Calibration procedure Kalibrierverfahren	IEC 61400-12-2:2017
Place of calibration Ort der Kalibrierung	Wind tunnel 2 of German Windguard Wind Tunnel Services GmbH, Varel
Test conditions Messbedingungen	wind tunnel area10000 cm² DUT frontal area200 cm² diameter of mounting pipe33.7 mm blockage ratio¹⁾0.020 [-] software versionP_9.1.0 ¹⁾ Due to the special construction of the test section no blockage correction is necessary.
Ambient conditions Umgebungsbedingungen	air temperature(21.5 ± 0.4 °C) – (21.6 ± 0.4 °C) air pressure(977.9 ± 0.4) hPa – (977.8 ± 0.4) hPa relative air humidity(55.2 ± 0.6) % – (55.3 ± 0.6) %
Measurement uncertainty Messunsicherheit	The expanded uncertainty associated to the measurement results is obtained by multiplying the standard uncertainty by the coverage factor $k=2$. It has been determined in accordance with EA-4/02-Mc:2013. The value of the measurement lies within the assigned range of values with a probability of 95%. The reference flow speed measurement is traceable to the German (NMJ) Physikalisch-Technische Bundesanstalt standard for flow speed. It is realized by using a PTB owned and calibrated Laser Doppler Anemometer (NMI) measuring uncertainty 0.2 %, $k=2$
Certificate ID Zertifikat ID	DIN.Krs.02.01.04-E0m7n7m 
Additional remarks Zusätzliche Anmerkungen	Calibration after refurbishment North alignment via north mark
Revision	0

(h) Wind vane 94012052, page 2/6

Calibration result (2/3)									
Calibration data (2/3)									
Alt. velocity	Reference	Reference	Reference	Combined	Test item	Test item	Test item	Test item	Test item
(m/s)	Unc.	Yaw angle	Unc.	Unc.	Direction	Angle	Angle	Angle	Deviation
0.04	0.04	259.96	0.80	1.12	159.83	-1.15			
0.05	0.04	164.45	0.80	1.12	164.75	-0.30			
0.05	0.04	169.89	0.80	1.12	169.89	-0.25			
0.05	0.04	174.97	0.80	1.12	174.67	-0.30			
0.05	0.04	179.96	0.80	1.12	179.56	-0.39			
0.04	0.04	184.97	0.80	1.12	184.75	-0.42			
0.04	0.04	190.01	0.80	1.12	189.63	-0.41			
0.04	0.04	195.02	0.80	1.12	194.61	-0.41			
0.04	0.04	200.03	0.80	1.12	199.62	-0.41			
0.05	0.04	204.99	0.80	1.12	204.65	-0.34			
0.05	0.04	209.98	0.80	1.12	209.68	-0.30			
0.05	0.04	214.95	0.80	1.12	214.89	-0.06			
0.05	0.04	219.93	0.80	1.12	219.96	-0.17			
0.04	0.04	224.96	0.80	1.12	224.83	-0.12			
0.04	0.04	230.00	0.80	1.12	229.92	-0.08			
0.05	0.04	234.98	0.80	1.12	234.90	-0.08			
0.04	0.04	239.90	0.80	1.12	239.85	-0.05			
0.05	0.04	244.90	0.80	1.12	244.82	-0.07			
0.05	0.04	249.88	0.80	1.12	249.85	-0.03			
0.05	0.04	254.97	0.80	1.12	254.87	-0.10			
0.05	0.04	259.96	0.80	1.12	259.81	-0.15			
0.04	0.04	264.98	0.80	1.12	264.68	-0.19			
0.06	0.04	270.03	0.80	1.12	269.76	-0.27			
0.04	0.04	275.01	0.80	1.12	274.75	-0.26			
0.05	0.04	279.97	0.80	1.12	279.71	-0.26			
0.05	0.04	284.97	0.80	1.12	284.70	-0.28			
0.05	0.04	289.99	0.80	1.12	289.71	-0.28			
0.05	0.04	295.00	0.80	1.12	294.78	-0.22			
0.05	0.04	300.01	0.80	1.12	299.84	-0.17			
0.05	0.04	305.02	0.80	1.12	304.87	-0.15			
0.05	0.04	309.99	0.80	1.12	309.84	-0.15			

Deutsche WindGuard Wind Tunnel Services GmbH
Oldenburgerstr. 65, D-26316 Varel

(j) Wind vane 94012052, page 4/6



(k) Wind vane 94012052, page 5/6



(l) Wind vane 94012052, page 6/6

DEUTSCHE WINDGUARD
IECRE and MEASNET approved test laboratory

Calibration Certificate / Kalibrierschein
issued by the calibration laboratory / erstellt durch das Kalibrierlaboratorium

Deutsche WindGuard
Wind Tunnel Services GmbH

Member of / Mitglied im
Deutschen Kalibrierdienst

accredited to / akkreditiert nach
DIN EN ISO/IEC 17025:2018

Object
Gegenstand Wind Vane

Manufacturer
Hersteller Thies Clima
D-37083 Göttingen

Type
Typ 4.3150.00.400

Serial number
Fabrikat/Serien-Nr. 02110032

Customer
Auftraggeber TNO
2302 JE The Hague - The Netherlands

Order No.
Auftragsnummer 3100333195

Project No.
Projektnummer VT220167

Number of pages
Anzahl der Seiten 6

Date of Calibration
Datum der Eichleistung 07.04.2022

This calibration certificate documents the traceability to national standards, which realize the units of measurement according to the International System of Units (SI). The DAKKS is signatory to the multilateral agreements of the European co-operation for Accreditation (EA) and of the International Laboratory Accreditation Cooperation (ILAC) for the mutual recognition of calibration certificates. The presented results relate only to the calibrated object. The user is obliged to have the object recalibrated at appropriate intervals. Dieser Kalibrierschein dokumentiert die Rückführung auf nationale Normale zur Darstellung der Einheiten in Übereinstimmung mit dem internationalen Einheitensystem (SI). Die DAKKS ist Unterzeichner der multilateralen Übereinkommen der Europäischen Zusammenarbeit für Akkreditierung (EA) und der Internationalen Laboratoriumszusammenarbeit (ILAC) zur gegenseitigen Anerkennung der Kalibrierscheine. Die dargestellten Ergebnisse beziehen sich nur auf den kalibrierten Gegenstand. Für die Einhaltung einer angemessenen Frist zur Wiederholung der Kalibrierung ist der Benutzer verantwortlich.

Calibration mark
Kalibrierzeichen

2221201
D-4-
15140-01-00
04/2022

Signature
Unterschrift

Date
Datum 07.04.2022

Signature
Unterschrift

Date
Datum 07.04.2022

Signature
Unterschrift

Date
Datum 07.04.2022

(m) Wind vane 94012461, page 1/6

Page 3 / 6
Seite

2221201
D-4-
15140-01-00
04/2022

Calibration result (1/3)
Kalibrierergebnis (1/3)

Reference	Reference	Reference	Reference	Combined	Test item	Test item
Air velocity	Unc	Yaw angle	Unc	Unc	Direction	Deviation
m/s	m/s	deg	deg	deg	deg	deg
8.01	0.04	5.00	0.80	1.11	5.54	0.54
8.01	0.04	10.02	0.80	1.11	10.49	0.46
8.01	0.04	14.95	0.80	1.11	15.35	0.40
8.02	0.04	19.88	0.80	1.11	20.45	0.46
8.01	0.04	24.98	0.80	1.11	25.46	0.48
8.02	0.04	30.02	0.80	1.11	30.57	0.55
8.02	0.04	35.02	0.80	1.11	35.63	0.61
8.02	0.04	39.65	0.80	1.11	40.34	0.69
8.02	0.04	44.95	0.80	1.12	45.68	0.73
8.02	0.04	49.95	0.80	1.12	50.67	0.72
8.02	0.04	55.01	0.80	1.12	55.79	0.77
8.01	0.04	59.99	0.80	1.12	60.80	0.81
8.01	0.04	65.03	0.80	1.12	65.80	0.77
8.01	0.04	70.05	0.80	1.12	70.77	0.73
8.01	0.04	75.01	0.80	1.12	75.70	0.70
8.01	0.04	79.91	0.80	1.12	80.55	0.64
8.01	0.04	84.93	0.80	1.12	85.49	0.56
8.02	0.04	90.04	0.80	1.12	90.55	0.51
8.02	0.04	95.06	0.80	1.12	95.47	0.41
8.01	0.04	100.02	0.80	1.12	100.47	0.44
8.01	0.04	105.01	0.80	1.12	105.49	0.47
8.02	0.04	110.00	0.80	1.12	110.50	0.51
8.01	0.04	115.02	0.80	1.12	115.54	0.53
8.02	0.04	120.00	0.80	1.12	120.58	0.58
8.01	0.04	125.01	0.80	1.12	125.64	0.61
8.01	0.04	130.05	0.80	1.12	130.71	0.66
8.01	0.04	135.02	0.80	1.12	135.77	0.75
8.01	0.04	139.92	0.80	1.12	140.69	0.77
8.02	0.04	144.96	0.80	1.12	145.80	0.84
8.01	0.04	149.94	0.80	1.12	150.79	0.85
8.02	0.04	154.95	0.80	1.12	155.79	0.84

Deutsche WindGuard Wind Tunnel Services GmbH
Oldenburgerstr. 65, D-26316 Varel

DEUTSCHE WINDGUARD

(o) Wind vane 94012461, page 3/6

Page 2 / 6
Seite

2221201
D-4-
15140-01-00
04/2022

Calibration object
Kalibriergegenstand Wind Vane

Calibration procedure
Kalibrierverfahren IEC 61400-12-3:2017

Place of calibration
Ort der Kalibrierung Wind tunnel 2 of Deutsche WindGuard Wind Tunnel Services GmbH, Varel

Test conditions
Messbedingungen

wind tunnel area 10000 cm²
DUT frontal area 200 cm²
diameter of mounting pipe 33.7 mm
blockage ratio ¹⁾ 0.020 [-]
software version P_9.1.0
¹⁾ Due to the special construction of the test section no blockage correction is necessary.

Ambient conditions
Umgebungsbedingungen

air temperature (21.6 ± 0.4) °C – (21.7 ± 0.4) °C
air pressure (977.5 ± 0.4) hPa – (978.1 ± 0.4) hPa
relative air humidity (35.2 ± 6.0) % – (35.3 ± 6.0) %

Measurement uncertainty
Messunsicherheit

The expanded uncertainty assigned to the measurement results is obtained by multiplying the standard uncertainty by the coverage factor $k=2$. It has been determined in accordance with EA-4/02:MC:2013. The value of the measured lies within the assigned range of values with a probability of 95%.
The reference flow speed measurement is traceable to the German 1001 (Physikalisch-Technische Bundesanstalt) standard for flow speed. It is realized by using a PTB owned and calibrated Laser Doppler Anemometer (Expanded uncertainty 0.2 %, $k=2$)

Certificate ID
Zertifikat-ID CqYPR7wFvRtGpX0CZ5649jd

Additional remarks
Zusätzliche Anmerkungen Calibration after refurbishment
North alignment via north mark

Revision
Revision 0

Deutsche WindGuard Wind Tunnel Services GmbH
Oldenburgerstr. 65, D-26316 Varel

DEUTSCHE WINDGUARD

(n) Wind vane 94012461, page 2/6

Page 4 / 6
Seite

2221201
D-4-
15140-01-00
04/2022


Calibration result (2/3)
Kalibrierergebnis (2/3)

Reference	Reference	Reference	Reference	Combined	Test item	Test item
Air velocity	Unc	Yaw angle	Unc	Unc	Direction	Deviation
m/s	m/s	deg	deg	deg	deg	deg
8.01	0.04	160.00	0.80	1.12	160.80	0.80
8.02	0.04	164.99	0.80	1.12	165.72	0.73
8.01	0.04	170.03	0.80	1.12	170.73	0.70
8.02	0.04	174.99	0.80	1.12	175.66	0.67
8.02	0.04	180.06	0.80	1.12	180.66	0.59
8.02	0.04	185.05	0.80	1.12	185.62	0.58
8.01	0.04	190.00	0.80	1.12	190.55	0.56
8.02	0.04	195.05	0.80	1.12	195.62	0.57
8.00	0.04	200.01	0.80	1.12	200.57	0.56
8.02	0.04	204.97	0.80	1.12	205.55	0.56
8.01	0.04	209.99	0.80	1.12	210.64	0.66
8.02	0.04	215.01	0.80	1.12	215.70	0.70
8.01	0.04	220.00	0.80	1.12	220.75	0.75
8.01	0.04	225.01	0.80	1.12	225.78	0.77
8.02	0.04	230.02	0.80	1.12	230.81	0.79
8.02	0.04	234.96	0.80	1.12	235.81	0.85
8.01	0.04	239.92	0.80	1.12	240.73	0.81
8.01	0.04	244.98	0.80	1.12	245.79	0.81
8.02	0.04	250.00	0.80	1.12	250.82	0.82
8.02	0.04	255.00	0.80	1.12	255.78	0.78
8.01	0.04	260.00	0.80	1.12	260.73	0.74
8.01	0.04	265.00	0.80	1.12	265.70	0.69
8.02	0.04	270.03	0.80	1.12	270.69	0.67
8.02	0.04	274.96	0.80	1.12	275.62	0.66
8.02	0.04	280.07	0.80	1.12	280.69	0.62
8.02	0.04	284.98	0.80	1.12	285.62	0.64
8.02	0.04	290.03	0.80	1.12	290.67	0.65
8.02	0.04	295.04	0.80	1.12	295.73	0.69
8.02	0.04	300.00	0.80	1.12	300.70	0.70
8.02	0.04	305.01	0.80	1.12	305.78	0.71
8.02	0.04	310.03	0.80	1.12	310.84	0.80

Deutsche WindGuard Wind Tunnel Services GmbH
Oldenburgerstr. 65, D-26316 Varel

DEUTSCHE WINDGUARD

(p) Wind vane 94012461, page 4/6



(q) Wind vane 94012461, page 5/6



(r) Wind vane 94012461, page 6/6

B.1.3 Relative humidity and temperature

  	
Vaisala is ISO 9001 and ISO 14001 certified company. MEASUREMENT STANDARDS LABORATORY ACCREDITED CALIBRATION LABORATORY	
CERTIFICATE OF CALIBRATION no K008-G03619	
Customer	TNO
Instrument	Humidity and Temperature Probe
Manufacturer	Vaisala Oy
Model	HMP155E
Serial number	M1141112
Instrument number	94012136
Calibration date	From June 12 to 13, 2023
Calibration due date	August 12, 2024
Issue date	June 13, 2023
Signature	 Jarmo Suutari Calibration Engineer
Page 1 (4)	
Documents attached	-
NOTES	The instrument was adjusted during calibration.
Conditions when received	Reported in Service Report.
This Certificate may not be reproduced in full, except with the prior written permission by the Issuing Laboratory. The measurement certificate and the Certificates of Calibration issued by an Accredited Calibration Laboratory comply with the measurement ranges and uncertainties approved by FINAS Finnish Accreditation Service. The measurement results issued by the Laboratory are traceable to national or international measurement standards. Measurement Standards Laboratory of Vaisala Oy is a calibration laboratory K008 accredited by FINAS Finnish Accreditation Service, accreditation requirement ISO/IEC 17025. The accreditation is included in the Multilateral Agreement (BIPM, ILAC) or the European cooperation for Accreditation (EAP).	
Vaisala Oy PO Box 28, FI-02421 Vammala, Finland Telephone: +358 9 255 1111 Fax: +358 9 255 1112 Email: replies@vaisala.com - www.vaisala.com Vaisala Group: www.vaisala.com	

VAISALA

Certificate number: K008-003619 Page 3 of 12

TEMPERATURE CALIBRATION

The temperature calibration was done in the Measurement Standards Laboratory (MSL) of Vaisala Oyj on June 12 and 13, 2023.

The temperature readings of the instrument were compared to the values of the reference thermometer from -34.4 °C to 54.4 °C in a climate chamber.

During calibration the instrument was allowed to stabilize to the conditions of the measurement temperature for at least 30 minutes.

Temperature values were read via serial port with resolution of 0.01 °C.

Temperature values are given according to the International Temperature Scale of 1990, ITS-90.

Measurement results

The reference and the reading values are averages of at least ten independent observations.

Reference [°C]	Reading T [°C]	Correction [°C]	Uncertainty [°C]	Specification [°C]	Conformity Statement
-34.35	-34.40	0.05	0.07	0.26	PASS
23.17	23.00	0.17	0.07	0.11	FAIL
54.62	54.41	0.21	0.07	0.11	FAIL

The correction should be added algebraically to the reading.

Reference [°C]	Reading T [°C]	Correction [°C]	Uncertainty [°C]	Specification [°C]	Conformity Statement
-34.35	-34.34	-0.01	0.07	0.26	PASS
23.17	23.17	0.00	0.07	0.11	PASS
54.62	54.63	-0.01	0.07	0.11	PASS

The correction should be added algebraically to the reading.

Figure 1: Final results, temperature [°C]

(a) RHT 94012136, page 1/2

(b) RHT 94012136, page 2/2

B.1.4 Air pressure

  	
Vaisala is ISO 9001 and ISO 14001 certified company MEASUREMENT STANDARDS LABORATORY ACCREDITED CALIBRATION LABORATORY	
Finnish Accreditation Service K008 (EN ISO/IEC 17025)	
CERTIFICATE OF CALIBRATION no K008-G03622	
Customer	TNO
Instrument	Pressure Transmitter
Manufacturer	Vaisala Oy
Model	PTB210A
Serial number	H1220002
Instrument number	94012651
Calibration date	On June 13, 2023
Calibration due date	August 13, 2024
Issue date	June 13, 2023
Signature	 (Ikka Kotamäki) Technical Manager
Page 1 (3)	
Documents attached	-
NOTES	Adjusted.
Conditions when received: Reported in Service Report.	
This Certificate may be reproduced in full, except with the prior written permission by the issuing Laboratory. The measurements were carried out and the Certificate of Calibration issued by an Accredited Calibration Laboratory comply with the measurement regime and underwritten guarantee by FINAS Finnish Accreditation Service. The measurement results issued by the Laboratory are fully traceable to national or international measurement standards. Measurement Standards Laboratory of Vaisala Oy is a calibration Laboratory K008 underwritten guarantee by Finnish Accreditation Service, accreditation requirement ISO/IEC 17025. The accreditation is included in the Multilateral Agreement (EA MRA) of the European co-operation for Accreditation (EA).	
Vaisala Oyj, PO Box 26, FI-02421 Vaisala, Finland Telephone: +358 9 856 311 • Fax: +358 9 856 2227 Email: info@vaisala.com • www.vaisala.com Domicile, Legal Address: Valtatie 102, FI-02421 Vaisala • Business ID 01244-16-2	

VAISALA

Certificate number K008-036622 Page 3 (of 3)

FINAL RESULTS

The reference and the reading values presented in table 2 are averages of ten independent observations. The results are averages of the measured two pressure cycles.

Table 2. Final results

Reference [hPa]	As found Calculated [hPa]	Correction [hPa]	As left Calculated [hPa]	Correction [hPa]	Uncertainty [hPa]
1100.01	1100.01	0.00	1100.02	-0.01	0.08
1050.01	1049.98	0.03	1049.99	0.02	0.08
1000.02	1000.01	0.01	1000.03	-0.01	0.08
950.03	950.00	0.03	950.02	0.01	0.08
900.04	899.91	0.13	899.94	0.10	0.08
850.15	850.13	0.02	850.17	-0.01	0.08
800.29	799.75	0.04	800.30	-0.01	0.08
750.41	750.39	0.02	750.41	0.00	0.08
700.46	700.39	0.07	700.45	0.01	0.09

The correction must be added algebraically to the reading.

Figure 1. Final results

Figure 1. Final results

(a) Air pressure sensor 94012651, page 1/2

(b) Air pressure sensor 94012651, page 2/2

B.1.5 Sonic 3D

DEUTSCHE WINDGUARD
Deutsche WindGuard
Wind Tunnel Services GmbH IECRE and MEASNET approved test laboratory

accredited by the / akkreditiert durch die
Deutsche Akkreditierungsstelle GmbH
as calibration laboratory in the / als Kalibrierlaboratorium im
Deutschen Kalibrierdienst

Calibration certificate
Kalibrierschein

Calibration mark
Kalibrierzeichen

Object
Objekt
3D Sonic Anemometer

Manufacturer
Hersteller
METEK GmbH
D-25337 Elmshorn

Type
Typ
USONIC-3 BASIC

Serial number
Faktisch-Gewinn-Nr.
0100074061
DEMOC203

Customer
Auftraggeber
TNO
2509 JE The Hague - The Netherlands

Order No.
Auftragsnummer
1114-01

Project No.
Projektnummer
VT181106

Number of pages
Anzahl der Seiten
6

Date of Calibration
Datum der Kalibrierung
28.11.2018

This calibration certificate may not be reproduced other than in full except with the permission of both the German Accreditation Body and the issuing laboratory. Calibration certificates without signature are not valid. This calibration certificate has been generated electronically.
Dieser Kalibrierschein darf nur vollständig und unverändert weiterverbreitet werden. Auszüge oder Änderungen bedürfen der Genehmigung sowohl der Deutschen Akkreditierungsstelle als auch des ausstellenden Kalibrierlaboratoriums. Kalibrierscheine ohne Unterschrift haben keine Gültigkeit. Dieser Kalibrierschein wurde elektronisch erzeugt.

Date
Datum
28.11.2018

Head of the calibration laboratory
Leitender Kalibrierlaboratoriums
Dipl. Phys. Dieter Windmann

Person in charge
Beauftragter
Kai Schuster, B. Eng.

(a) Sonic 3D 94012039, page 1/6

Page 3 / 6
Seite

1823950
D-K:
15140-01-00
11/2018

Reference	Reference	Test item	Test item	Test item
Air velocity	U _{ref}	x	y	z
m/s	m/s	m/s	m/s	m/s
3.985	0.05	-12.869	-403.688	32.156
6.017	0.05	-12.906	-411.469	1.231
8.009	0.05	-9.775	-414.688	-11.475
9.996	0.05	-2.225	-1002.731	-20.331
13.006	0.05	3.712	-1204.983	-26.981
15.920	0.05	7.956	-1303.244	-20.587
15.940	0.05	7.612	-1584.888	-34.350
15.016	0.05	5.844	-1500.188	-31.750
12.993	0.05	-1.175	-1306.844	-25.131
10.991	0.05	-8.806	-1111.888	-16.281
9.985	0.05	-16.111	-612.761	-6.825
7.003	0.05	-16.594	-711.594	-0.738
4.999	0.05	-14.856	-507.131	8.250

(c) Sonic 3D 94012039, page 3/6

Page 2 / 6
Seite

1823950
D-K:
15140-01-00
11/2018

Calibration object
Kalibrierungsgegenstand
3D Sonic Anemometer

Calibration procedure
Kalibrierverfahren
IEC 61400-12-1:2017

Place of calibration
Ort der Kalibrierung
Wind tunnel of Deutsche WindGuard WindTunnel Services GmbH, Varel

Test conditions
Messbedingungen

wind tunnel area
10000 cm²

anemometer frontal area
370 cm²

diameter of mounting pipe
43.0 mm EN 10217

blockage ratio ¹⁾
0.037 [-]

software version
P_7.8.07

¹⁾ Due to the special construction of the test section no blockage correction is necessary.

Ambient conditions
Umgebungsbedingungen

air temperature
20.5 °C ± 0.1 °C

air pressure
1020.2 hPa ± 0.3 hPa

relative air humidity
34.5 % ± 2.0 %

Measurement uncertainty
Messunsicherheit

The expanded uncertainty assigned to the measurement results is obtained by multiplying the standard uncertainty by the coverage factor $k=2$. It has been determined in accordance with DAkkS GUM 3. The value of the measured lies within the assigned range of values with a probability of 95%.

The reference flow speed measurement is traceable to the German NM1 (Physikalisch-Technische Bundesanstalt) standard for flow speed. It is realized by using a PTF owned and calibrated Laser Doppler Anemometer (Standard Uncertainty 0.2 %, $k=2$)

Additional remarks
Zusätzliche Anmerkungen

Orientation: 0°


(b) Sonic 3D 94012039, page 2/6

Page 4 / 6
Seite

1823950
D-K:
15140-01-00
11/2018

Photo of the measurement setup
Foto des Messaufbaus

28.11.2018 Cal No: 1823950 SN: 0100074061 / DEMOC203



Remark: The proportions of the set-up may not be true to scale due to imaging geometry.

(d) Sonic 3D 94012039, page 4/6

Page 5 / 6
Seite

1823950

046

15940-01-00

11/2018

Sensor config during calibration (1/2)

Sensorkonfiguration während der Kalibrierung (1/2)

C-7

RAD-D-0

RAE-D-0

RAO-D-0

RAT-D-0

RAV-D-0

RAZ-D-0

RBR-9600

REC-1

RFR-D-0

RHC-1

RHD-D-0

RHE-D-0

RHT-D-0

RLC-07.11.18 11:11:01

RMD-D-0

RND-0

RN1-REPCAL071118

RN2-REPCAL071118

RN3-REPCAL071118

RNO-31

RO1-2297

RO2-2279

RO3-2257

RO4-2256

RO5-2287

RO6-2284

ROA-D-0

ROD-1

RPI-1762

RPI-1762

RPI-1754

RPI-D-0

Deutsche WindGuard

Wind Tunnel Services GmbH, Varel

DEUTSCHE

WINDGUARD

(e) Sonic 3D 94012039, page 5/6

Page 6 / 6
Seite

1823950

046

15940-01-00

11/2018

Sensor config during calibration (2/2)

Sensorkonfiguration während der Kalibrierung (2/2)

RQT-D-0

RSA-D-0

RSR-20000

RSD-D-0

RSY-D-0

RTC-2200

RTI-28.11.18 10:27:24

RTN-6000

RTV-D-0

RVR-6000

RZB-100

Rversion 5.51b created at 13021745515 serial no. 0326074061

Deutsche WindGuard

Wind Tunnel Services GmbH, Varel

DEUTSCHE

WINDGUARD

(f) Sonic 3D 94012039, page 6/6

B.2 Thies cup classification sheet

Summary report of cup anemometer classification



Class S Classification Reference: IEC 61400-12-1 Edition 2.0 Wind Turbine Power Performance Testing 2017-03 Result: Figure showing the calculated total deviation of the Thies First Class Advanced anemometer type 4.3352.00.000 taking into account all influencing parameters according to Class S definition. Internal shaft heating ON Classification index: S 0.9 (average of five sensors)	FCA II - SN 01130001 - heating on
Class S Classification Reference: IEC 61400-12-1 Edition 2.0 Wind Turbine Power Performance Testing 2017-03 Result: Figure showing the calculated total deviation of the Thies First Class Advanced anemometer type 4.3352.00.000 taking into account all influencing parameters according to Class S definition. Internal shaft heating OFF Classification index: S 1.7 (average of five sensors)	FCA II - SN 01130001 - heating off

Energy & Materials Transition

Westerduinweg 3
1755 LE Petten
www.tno.nl