Title

Ref. no.

: 88-054

File no.

: 8725-19335

Publ. no.

: CB/054

Date

: February 1988

PRODUCTS MOVING IN COLD CHAINS

MODELLING TEMPERATURE DISTRIBUTION IN

Publication

Author(s):

R.J.M. van Gerwen

Presented at the I.I.F.-I.I.R. meeting of commissions B1, B2, C2, D1, D2, D3 - Wageningen (The Netherlands) - 1988.

MODELLING TEMPERATURE DISTRIBUTION IN PRODUCTS MOVING IN COLD CHAINS

R.J.M. van Gerwen
Department of Heat and Refrigeration Technology
The Netherlands organization for applied scientific research TNO
Apeldoorn (The Netherlands)

1. INTRODUCTION

Computer simulation is a well-known technique for the assessment of the thermal behaviour of products moving in cold chains.

The computer package BERTEM has been developed for computations of the time dependent temperature distribution in inhomogeneous solids and fluid flows of arbitrary geometry.

In this paper a description of this package is presented and some successful applications are mentioned. The use of the BERTEM package for computations of the temperature distributions in pig carcasses is described in detail.

The scope of this paper has been restricted to the technical aspects. The economic aspects have already been discussed by Moerman [7]. In general terms the tools for accurate computations of the temperature distribution in products moving in cold chains can contribute to the optimization of the cold chain in economic respect.

2. COMPUTER PACKAGE "BERTEM"

2.1 Background

The computer package BERTEM has been based on the finite element method (FEM); solid and fluid flow are divided into elements of arbitrary shape. This technique has been discussed in detail by Comini [1] and Cleland [2], [3].

FEM is a very flexible and universal method: inhomogeneous multi-dimensional shapes

FEM is a very flexible and universal method: inhomogeneous multi-dimensional shapes of irregular geometry can be handled. An other well-known method based on finite differences (FDM) is limited by practical considerations to use for one-dimensional and regular multi-dimensional shapes where evenly spaced grids can be used. However, the flexibility of FEM can lead to excessive computation costs. In the case of BERTEM this disadvantage is countered thanks to the adaptation to the purpose of the computations, which leads to a reduction of computation time and costs. Thus BERTEM is more suited for those calculations than general purpose computer packages like PHOENICS (Spalding [4]).

2.2 Thermal model

The solid and/or fluid flow is divided into elements of an arbitrary geometry (one, two or three dimensions).

An element can represent a thermal mass, a flow part, a junction of flows, a boundary or an interpolation of temperatures of neighbour-elements.

The elements can be characterised by a heat capacity, an internal heat generation or a latent heat, temperature dependent if required.

All elements are linked by connectors between the central points of the elements, representing the heat or fluid flow between them.

2.3 Computation and 2012

The temperatures of all the sleep at are conscured by the tandanimelity stable integration permiss i.e. a combination of infort-Frankel, d.and-Mis. wheel and an extrapolation section, so the choice of the suputation clime integral will only affect the accuracy of the results.

If desired, the boundary conditions and computation time interval can be educated and intermediate results can be abinized during conjugations in an intersective session.

The proposal vaciouse had need medition in this FORTRAN ?? language for ise on mint computers and mainfrance decontry, a version for use on on [38 :0]%: [AT clampatible personal computer has been dem loped.

SMODIAGLITAN E

3.1 General applications

The computer pasking the been successfully used for aging a range of - capacing and temperature distribution of soil mest exchangers for seasonal thernemalicate Tempera


mar sterage;

- assessment and optilization of floor deating systems,

- capacity of the heating system of an old tank; - nemperature disa dention in the malls of brick kilns end above:

2.2 Applicacions on calrigeration angior ecing

RERTEM has also been used for savarel malgulations in the Held of thingstation in this context towestigations have been carried out into ventilates catgoes. The ergineering usefulness of the package for this application has been investigated by compering computations and measurements for a sell-seffined test-orse. Figure . shows a composine stack of pores falled with wover and with forced venfilation whitnesh the cravices. in figure 2, experimental as usui as computed results are shown There proved to be a satisfactory as sevent between them.



2.3 Computation method

The temperatures of all the elements are computed by the use of fundamentally stable integration methods, i.e. a combination of Dufort-Frankel, Crank-Nicholson and an extrapolation method, so the choice of the computation time interval will only affect the accuracy of the results.

If desired, the boundary conditions and computation time interval can be adjusted and intermediate results can be obtained during computations in an interactive session.

The program package has been written in the FORTRAN 77 language for use on mini computers and mainframes. Recently, a version for use on an IBM PC/XT/AT compatible personal computer has been developed.

3. APPLICATIONS

3.1 General applications

The computer package BERTEM has been successfully used for quite a range of thermal problems:

- capacity and temperature distribution of soil heat exchangers for seasonal thermal storage;

- assessment and optimization of floor heating systems;

- capacity of the heating system of an oil tank;

- temperature distribution in the walls of brick kilns and stoves.

3.2 Applications in refrigeration engineering

BERTEM has also been used for several calculations in the field of refrigeration engineering.

In this context investigations have been carried out into ventilated cargoes. The usefulness of the package for this application has been investigated by comparing computations and measurements for a well-defined test-case.

Figure 1 shows a composite stack of boxes filled with water and with forced ventilation through the crevices.

In figure 2, experimental as well as computed results are shown. There proved to be a satisfactory agreement between them.




Fig. 1 - Composite stack of boxes.




Fig. 2 - Measured and computed temperatures in the boxes of a composite stank. Must temperature jump from $J_{\rm c}/S^2 {\rm Co}/S^2 {\rm Co}$

Van de Rea (5) has described computations of the temperature distribution in pentilated cargoes in relation to the air direction during, birth proves to be a pasful tool.

All comparties not as been made between WERTEM and in other ecopater program, based on the Finite Difference Method (FDM), while the confiner and treezing three of a horogeneous rectangular brick filled with water have been companed.

The compared results are summarized in Table 1.

The differences between the results of both of the computer programs are within 13. However, the computation by BERTIM has taken 14% of the needed by the fine program.

ocentroper IABLE I Comparison of computer programs

(Mallymore A) 1 - Horself as	475		BERTEM		
	25		Ça .	n sime interval (1)	
	3992	14	90%	ce 'hou'est eiement 'O; Le (houtest eiement	reachas 25-
	UNRIS		38315		c- sectoses.
-	570,000		558,000	- (1) mainto y quens	
	2.71	1 1	-17.2	O' deserge s-elisa io a	
	0041	-	200		consultation

- number of elementics 125 (1/5 of a brick)
- thermal conductivity and specific heat capacity of water
 - brick dimensions: (.i x 0.1 x 0.1 m3
 - surface hear transfer coefficient: 30 $m We^{-2}K^{-1}$
 - initioi temperature : 30°C
 - ambient wir temperature: -20°C
- a shorter time interval or extension of the sumber of elements 4 4 and affect, the results afguildently

in the core chapter the applibunting of dERTEM for computerions on the camperature distribution is slaughteredopigales discussed asserbate.




Fig. 2 - Measured and computed temperatures in the boxes of a composite stack. Air temperature jump from 7.5°C to 30.5°C.

Van de Ree [5] has described computations of the temperature distribution in ventilated cargoes in relation to the air circulation number. BERTEM proved to be a useful tool.

A comparison has been made between BERTEM and an other computer program, based on the Finite Difference Method (FDM), Cleland [6]. The cooling- and freezing times of a homogeneous rectangular brick filled with water have been computed.

The computed results are summarized in Table I.

The differences between the results of both of the computer programs are within 1%.

However, the computation by BERTEM has taken 14% of the time needed by the FDM program.

TABLE I Comparison of computer programs

	MANUFACTURE CO. V AND RECORD WITH A PROPERTY OF A PARTY	BERTEM	FDM
calculation time interval	(s)	40	25
cooling time (hottest element reaches 25°C)	(s)	2400	2400
freezing time (hottest element reaches -5°C)	(s)	21280	21500
change in energy content	(J)	568,000	570,000
temperature of coldest element	(°C)	-17.2	-17.9
computation time	(s)	200	1400

- number of elements: 125 (1/8 of a brick)
- thermal conductivity and specific heat capacity of water
- brick dimensions: 0.1 x 0.1 x 0.1 m³
- surface heat transfer coefficient: 30 $Wm^{-2}K^{-1}$
- initial temperature : 50°C
- ambient air temperature: -20°C
- a shorter time interval or extension of the number of elements did not affect the results significantly

In the next chapter the application of BERTEM for computations of the temperature distribution in slaughtered pigs is discussed in detail.


=.1 Background

According to the EC-regulations for tresh meat, carcasses shell be chilled after slaughter to an internal camperature of 73C or lower retors being transported to other countiles in the Common Market. The aim of the investigations was to study the influence of transport on the temperature distribution and become condition of helf pig carcasses before the indernative caperature roaches 7°C. Moreover the conditions has to be formulated under which such a transport could be allowed to be carried out taking the required hysiemic quality of the meat into account. These investigations have been partied out in co-operation with EMO-CIVO Food Tachnology Institute. Werderlands Cambre for Meat Sections are described in detail by

The thermal investigations consisted of the construction of a finite element model of half a properties as a part of the DFRTEM computer package, temperature assertiements during several test transports in order to validate the nodel and computations with BERTEM for a lot of storage and transport cases. In the near paragraphs this will be discussed in more detail.

4.2 Model set up

A finite element model of half a pig carcaes has been designed by dividing the carcaes in 338 oubin elements of 5 m 5 m 5 m. Three types of elements have been used; bone, far and meat with corresponding thermal properties, the special geometry of the computation model has been determined by cutting a real carcaes into slaps of 5 cm thickness (see tigure 5).



High Boundar section of cardene model.

4.1 Background

According to the EC-regulations for fresh meat, carcasses shall be chilled after slaughter to an internal temperature of 7°C or lower before being transported to other countries in the Common Market. The aim of the investigations was to study the influence of transport on the temperature distribution and bacteriological condition of half pig carcasses before the internal temperature reaches 7°C. Moreover the conditions had to be formulated under which such a transport could be allowed to be carried out taking the required hygienic quality of the meat into account. These investigations have been carried out in co-operation with TNO-CIVO Food Technology Institute, Netherlands Centre for Meat Technology and are described in detail by Moerman [7].

The thermal investigations consisted of the construction of a finite element model of half a pig carcass as a part of the BERTEM computer package, temperature measurements during several test transports in order to validate the model and computations with BERTEM for a lot of storage and transport cases. In the next paragraphs this will be

discussed in more detail.

4.2 Model set up

A finite element model of half a pig carcass has been designed by dividing the carcass in 338 cubic elements of $5 \times 5 \times 5 \text{ cm}^3$. Three types of elements have been used: bone, fat and meat with corresponding thermal properties. The spacial geometry of the computation model has been determined by cutting a real carcass into slabs of 5 cm thickness (see figure 3).




Fig. 3 - Cross section of carcase model.


Flow and boundary elements represent the airflow around the carcass.


The design of such a model is a rather rise-consuming affair; on the order hand the computations with time and position dependent initial and boundary talacts are very easy to carry our

The carcass model has been incorporated at the SZRIEM paakage. Combined with input concerning intrial and houndary values, the care dependent texperature distribution, heat content and the beat emission of the pig carcass are concent.

4,5 Experimental maiddetion

The conversions distribution in a pig carders has been descured during a large part of the cold chain. An exemple of the squedimental results as well as the km-puted results ich an identical dass are presented in figure 4. \
In figure 5 the measured and calculated temperatures are compared. The results show a good agreement and justify the usefulness for other computations.








Fig. 5 - Relation between computer and measures values.

4.4 Computations and casults

The temperature distribution in oig sarcasses and the related heat emission have been concuted for a range of precesses with transport lesore and atter the internal temperature has reached 7°C.

The computations show what time, air temperature, air relocary and rafrigarating capacity are required during the rudocasive phases of the sold chain, to obtain the desired time-temperature course in a ply carcass.

As an over-all result of the study, the corditions have been determined to allow transport of pig chickses becove the internal lamperature reaches $7^{\circ}C_{\circ}$.

These conditions have been accepted by the Larch authorities for intend transports Computations with the BERIPM package form part of the procedure for granting a literoe. In this care, the use of computer simulation leads to a drastic reduction of time and costs because of a strong raduction of required measurements and the possibility of optimizing the cold chain.

4.5 Anggestions for other appliantions

The scheme described in the pressous paragraphs is also applicable for other products. The restor do amanerally suited for computations of competencine discributions in the manager and treguler traped bedies such as shape and broken carecasts, politry or paint with fructor vecetables.

The design of such a model is a rather time-consuming affair; on the other hand the computations with time and position dependent initial and boundary values are very easy to carry out.

The carcass model has been incorporated in the BERTEM package. Combined with input concerning initial and boundary values, the time dependent temperature distribution, heat content and the heat emission of the pig carcass are computed.

4.3 Experimental validation

The temperature distribution in a pig carcass has been measured during a large part of the cold chain. An example of the experimental results as well as the computed results for an identical case are presented in figure 4.

In figure 5 the measured and calculated temperatures are compared. The results show a good agreement and justify the usefulness for other computations.




Fig. 4 - Computations and measurements for a test-case.




Fig. 5 - Relation between computed and measured values.

4.4 Computations and results

The temperature distribution in pig carcasses and the related heat emission have been computed for a range of practical cases with transport before and after the internal temperature has reached 7°C.

The computations show what time, air temperature, air velocity and refrigerating capacity are required during the successive phases of the cold chain, to obtain the desired time-temperature course in a pig carcass.

As an over-all result of the study, the conditions have been determined to allow transport of pig carcasses before the internal temperature reaches 7°C.

These conditions have been accepted by the Dutch authorities for inland transport. Computations with the BERTEM package form part of the procedure for granting a licence. In this case, the use of computer simulation leads to a drastic reduction of time and costs because of a strong reduction of required measurements and the possibility of optimizing the cold chain.

4.5 Suggestions for other applications

The scheme described in the previous paragraphs is also applicable for other products. The method is eminently suited for computations of temperature distributions in inhomogeneous and irregular shaped bodies such as sheep and bovine carcasses, poultry or pallets with fruit or vegetables.

5. CONCLUSIONS

- The computer package BERTEM has been developed for computations of the time dependent temperature distribution in inhomogeneous solids and fluid flows of arbitrary shape.
- The package has been successfully applied for a range of thermal problems.
- In the field of refrigeration engineering BERTEM has been used for computations related to ventilated cargoes and cooling or freezing of solids, surrounded by fluid flow (e.g. air).
- The computer package has showed to be a very appropriate tool for the computation of temperature distributions in pig carcasses. The method is eminently suited for computations and irregular shaped bodies such as sheep and bovine carcasses, poultry or pallets with fruit or vegetables.

REFERENCES

- [1] G. Comini et al; The finite element method in refrigeration engineering; Int. Journal of Refrigeration (1978), 2.
- [2] D.J. Cleland et al; Prediction of rates of freezing, thawing or cooling in solids of arbitrary shape using the finite element method; Int. Journal of Refrigeration (1984), 1.
- [3] D.J. Cleland et al; Prediction of freezing and thawing times for multi-dimensional shapes by numerical methods; Int. Journal of Refrigeration (1987), 1.
- [4] D.B. Spalding; General purpose computer program for multi-dimensional 1- and 2-phase flow; Journal of Mathematics and computers in Simulation (1981), pp. 267-276.
- [5] H. van de Ree et al; Prediction of temperature distributions in cargoes with the aid of a computer program using the method of finite elements; IIF-IIR-commission D2, Wageningen, 1974-2.
- [6] A.C. Celand; RADS - a computer package for refrigeration analysis, design and simulation; Int. Journal of Refrigeration (1985), 11.
- [7] P.C. Moerman; Experience with quick chilling and transport of pig carcasses; I.I.F.-I.I.R.-commission C2, Bristol, 1986-3.


MODELER LA RÉPARTITION DES TEMPÉRATURES DANS LES PRODUITS MOUVANT EN CHAÎNE FRIGORIFIQUE


RÉSUMÉ: Le programme d'ordinateur BERTEM a été développé pour calculer la répartition des températures dans des solides de géometrie quelconque avec des propriétés variables.

Le programme s'appuie sur la méthode des éléments finis.


On examine les caractéristiques du programme et on les illustre avec plusieurs examples d'application.


On décrit au détail l'usage du programme BERTEM pour calculer la répartition des températures dans les carcasses des couchons.
















measured temperature

















2.3 Computation method

The temperatures of all the elements are computed by the use of fundamentally stable integration methods, i.e. a combination of Dufort-Frankel, Crank-Nicholson and an extrapolation method, so the choice of the computation time interval will only affect the accuracy of the results.

If desired, the boundary conditions and computation time interval can be adjusted and intermediate results can be obtained during computations in an interactive session.

The program package has been written in the FORTRAN 77 language for use on mini computers and mainframes. Recently, a version for use on an IBM PC/XT/AT compatible personal computer has been developed.

APPLICATIONS

3.1 General applications

The computer package BERTEM has been successfully used for quite a range of thermal problems:

- capacity and temperature distribution of soil heat exchangers for seasonal thermal storage;
- assessment and optimization of floor heating systems;
- capacity of the heating system of an oil tank;
- temperature distribution in the walls of brick kilns and stoves.

3.2 Applications in refrigeration engineering

BERTEM has also been used for several calculations in the field of refrigeration engineering.

In this context investigations have been carried out into ventilated cargoes. The usefulness of the package for this application has been investigated by comparing computations and measurements for a well-defined test-case.

Figure 1 shows a composite stack of boxes filled with water and with forced ventilation through the crevices.

In figure 2, experimental as well as computed results are shown. There proved to be a satisfactory agreement between them.





Fig. 1 - Composite stack of boxes.



To a trade of the second second			The second secon
The state of the same of the s			
			And the second s
	- 51.		or a firm of the firm of a firm of the fir
	₩.		. Carron Courtern) geste garbitation. Little description
			to a control of other than the market market and
	CAD, CVI		្រុក ក្រុមប្រជាពល ការ ស្មែកចំណាំ
	4.12.		ាំ ខ្លាំ ខ្លាំ ខ្លាំ នៅ រូបនៅ នេះស្នាច់ដ
man or the first of selecting cooks.			Julians and more

- this out the same of entered hid mor affocc




Fig. 2 - Measured and computed temperatures in the boxes of a composite stack. Air temperature jump from 7.5°C to 30.5°C.

Van de Ree [5] has described computations of the temperature distribution in ventilated cargoes in relation to the air circulation number. BERTEM proved to be a useful tool.

A comparison has been made between BERTEM and an other computer program, based on the Finite Difference Method (FDM), Cleland [6]. The cooling- and freezing times of a homogeneous rectangular brick filled with water have been computed.

The computed results are summarized in Table I.

The differences between the results of both of the computer programs are within 1%.

However, the computation by BERTEM has taken 14% of the time needed by the FDM

TABLE I
Comparison of computer programs

		BERTEM	FDM
calculation time interval	(s)	40	25
cooling time (hottest element reaches 25°C) freezing time (hottest element	(s)	2400	2400
reaches -5°C)	(s)	21280	21500
change in energy content	(J)	568,000	570,000
temperature of coldest element	(°C)	-17.2	-17.9
computation time	(s)	200	1400

- number of elements: 125 (1/8 of a brick)
- thermal conductivity and specific heat capacity of water
- brick dimensions: 0.1 x 0.1 x 0.1 m³
- surface heat transfer coefficient: 30 $\mathrm{Wm}^{-2}\mathrm{K}^{-1}$
- initial temperature : 50°C

program.

- ambient air temperature: -20°C
- a shorter time interval or extension of the number of elements did not affect the results significantly

In the next chapter the application of BERTEM for computations of the temperature distribution in slaughtered pigs is discussed in detail.

houngale-a i.s

According to the compact of the control of the cont

The statement of the state of the notification of the statement of the sta

40 591 10



Fritan mar anna en el laco en el laco

4.1 Background

According to the EC-regulations for fresh meat, carcasses shall be chilled after slaughter to an internal temperature of 7°C or lower before being transported to other countries in the Common Market. The aim of the investigations was to study the influence of transport on the temperature distribution and bacteriological condition of half pig carcasses before the internal temperature reaches 7°C. Moreover the conditions had to be formulated under which such a transport could be allowed to be carried out taking the required hygienic quality of the meat into account. These investigations have been carried out in co-operation with TNO-CIVO Food Technology Institute, Netherlands Centre for Meat Technology and are described in detail by Moerman [7].

The thermal investigations consisted of the construction of a finite element model of half a pig carcass as a part of the BERTEM computer package, temperature measurements during several test transports in order to validate the model and computations with BERTEM for a lot of storage and transport cases. In the next paragraphs this will be discussed in more detail.

4.2 Model set up

A finite element model of half a pig carcass has been designed by dividing the carcass in 338 cubic elements of $5 \times 5 \times 5 \text{ cm}^3$. Three types of elements have been used: bone, fat and meat with corresponding thermal properties. The spacial geometry of the computation model has been determined by cutting a real carcass into slabs of 5 cm thickness (see figure 3).




Fig. 3 - Cross section of carcase model.


Flow and boundary elements represent the airflow around the carcass.

Deud proble stir en frâgiske grûnsserne-boir asdaya e koleder i eber in agreek sdî' Sak i hiden Yorketon bræsk i folkli nostroch koledersy san i een fe'r archybourgoop sis dan ynter oa vere grad

The hercass which is even in importable in the ABS ABSC has been set to be set to be set to be a dependent to the constant dependent to the set of the set

with the Life of American Program See a

The state of the second control of the state of the second of the state of the



මුදුරු ම මාර්යකදාන දෙන සිතින සිතින සිතුන් මෙසේ සිතුන් සිතුන්

. I sus and rus dugmod - 2. A

a real results of the contract of contract of the contract of

1.5 Sugisations are the sugistical

The scheme case then in the privites peragrapes is also applies for other perducts for other perducts. In the second of strains of computations of the second distributes the first distributes of the second of the

The design of such a model is a rather time-consuming affair; on the other hand the computations with time and position dependent initial and boundary values are very easy to carry out.

The carcass model has been incorporated in the BERTEM package. Combined with input concerning initial and boundary values, the time dependent temperature distribution, heat content and the heat emission of the pig carcass are computed.

4.3 Experimental validation

The temperature distribution in a pig carcass has been measured during a large part of the cold chain. An example of the experimental results as well as the computed results for an identical case are presented in figure 4. In figure 5 the measured and calculated temperatures are compared. The results show a

good agreement and justify the usefulness for other computations.




Fig. 4 - Computations and measurements for a test-case.




Fig. 5 - Relation between computed and measured values.

4.4 Computations and results

The temperature distribution in pig carcasses and the related heat emission have been computed for a range of practical cases with transport before and after the internal temperature has reached 7°C.

The computations show what time, air temperature, air velocity and refrigerating capacity are required during the successive phases of the cold chain, to obtain the desired time-temperature course in a pig carcass.

As an over-all result of the study, the conditions have been determined to allow transport of pig carcasses before the internal temperature reaches 7°C.

These conditions have been accepted by the Dutch authorities for inland transport. Computations with the BERTEM package form part of the procedure for granting a licence. In this case, the use of computer simulation leads to a drastic reduction of time and costs because of a strong reduction of required measurements and the possibility of optimizing the cold chain.

4.5 Suggestions for other applications

The scheme described in the previous paragraphs is also applicable for other products. The method is eminently suited for computations of temperature distributions in inhomogeneous and irregular shaped bodies such as sheep and bovine carcasses, poultry or pallets with fruit or vegetables.



