

Alternative Method for Large Vacuum Systems Bake-out

TNO
Innovation for Life



CE/ET BEAMTUBE WORKSHOP III 2025

Freek Molkenboer, Han Velthuis, Herman Bekman, Andrey Ushakov, Véronique De Rooij, Thom Oosterveer, Michael Dekker, Corné Rijnsent, Willem van Werkhoven, Dirk van Baarle



Outline


- Intro TNO
- ~~• Gravitational waves~~
- ~~• Einstein Telescope and cosmic explorer~~
- ET MacBeth project
- An alternative method for large vacuum systems bake-out
- Conclusions and outlook

TNO – Semicon Equipment groups

- **TNO: Netherlands Organisation for Applied Scientific Research**
 - Established in 1932, non-profit organisation
 - Independent and confidential partner
 - 2024: ~4500 employees, ~764 MEUR organisation revenue



Campus TU-Delft, Delft



Philips High Tech Campus, Eindhoven



TNO High Tech Industry



APPLICATIONS


First MetOp-SG and Sentinel-5 launched

13/08/2025 6688 VIEWS 50 LIKES

[ESA / Applications / Observing the Earth / Meteorological missions / MetOp Second Generation](#)


Ushering in a new era of weather and climate monitoring from polar orbit, the first in a new series of satellites, MetOp Second Generation, has been lofted into orbit aboard an Ariane 6 rocket from the European spaceport in Kourou, French Guiana. As part of this new satellite's sophisticated instrument package is the new Copernicus Sentinel-5 instrument, which is designed to deliver critical data on air pollutants, ozone and climate-related gases.

Lifting off on 13 August at 02:37 CEST (12 August 21:37 local time), the Ariane 6 rocket carried the four-tonne satellite into orbit around Earth. Confirmation that MetOp-SG-A1 was alive and well came at 04:47 CEST, after its solar array had been deployed, ensuring that the satellite could generate power.



MacBeth Project

- Manufacturing and Cleanliness of Beampipe for Einstein Telescope in High-vacuum



MacBeth Project





Figure 3: Visualization of the Einstein Telescope and all process steps from manufacturing to installation

- Design and make pilot section of a corrugated beam-pipe
- Study:
 - How to do industrial scale with the required cleanliness levels
 - How to measure the cleanliness levels and the quality also at the industrial scale

Alternative method for large vacuum systems bake-out

- The challenge; surface absorbed water
- Current intended method for the Einstein Telescope
 - Joule heating with thermal insulation
 - 5 km at a time, re-use of thermal insulation

case it is a copper sheet with dimensions 5×20 cm, then intense copper lines appear in the spectrum (Fig. 15,b). As the working gas pressure increases (the pumping is only with fore pump), intense lines characteristic of water (OH) are detected in the spectra (Fig. 16), which is apparently due to the insufficient speed of the fore vacuum pumping of impurities. Note, the intensity of OH signal in combined discharges is higher than that for GD. It could say about more effective surfaces treatment with combined discharges. Over time, during discharge cleaning, the intensity of the water lines decreases (see Fig. 16,b) which is indication of the wall conditions improvement.



VACUUM-PLASMA PROPERTIES OF STAINLESS STEEL AFTER IMPACT OF COMBINED GLOW-MICROWAVE DISCHARGES IN ARGON ATMOSPHERE

G.P. Glazunov, V.E. Moiseenko, S.M. Maznichenko, M.N. Bondarenko, A.L. Konotopskiy,
I.K. Tarasov, A.N. Shapoval

Institute of Plasma Physics, National Science Center
"Kharkov Institute of Physics and Technology", Kharkiv, Ukraine
E-mail: glazunov@ipp.kharkov.ua





Fig. 16. Emission plasma spectra of glow and combined discharges during evacuation of the chamber by a fore pump (a); spectra of glow discharges vs a cleaning time



More literature

	Cleaning of Silicon Wafer Surfaces with Reactive Gases.pdf
☐	CombinedRF-DCP_plasmaDischargeCleaning.pdf
	CONDITIONING VACUUM Chambers.pdf
	DC Glow Discharge Between Coaxial Cylinders .pdf
	DC Glow Discharge Between Coaxial Cylinders 2.pdf
	DC Glow Discharge COMSOL.pdf
	DC Glow Discharge.pdf
	DC Glow Discharge2.pdf
	DC Glow Discharge3.pdf
	DC Glow Discharge4.pdf
	DC Glow Discharge5.pdf
	DC Glow Discharge6.pdf
	Modeling of glow discharge optical emission spectrometry.pdf
	OutgassingReductionTechniques1988.pdf
	OutgassingReductionTechniques1988_2.pdf
	Plasma Cleaning.pdf
	Plasma_Cleaning_of_Hydrocarbon_and_Carbon_Contamin.pdf
	Reactive Gas Plasma Cleaning.pdf
	ReactiveGases.pdf
	StainlessSteelGlowDischargeCleaning.pdf


	A Review of Outgassing and Methods for its Reduction.pdf
☐	jove-118-55017.pdf
	MeasOfOutgasData.pdf
	Readhead_EXTREME HIGH VACUUM.pdf
	WaterVaporInVacuumSystems.pdf

	10_Surface_Flashover_of_Alumina_Ceramic_Insulators_in_Vacuum.pdf
	8_s11090-019-09974-9.pdf
☐	dischagre_1mbar_N2_H2_Chatain_2023_Plasma_Sources_Sci._Technol._... ...
	Modelling and optimization of a low-pressure DC glow.pdf
	N10_s42774-021-00067-w.pdf
	N11_sab99comparison.pdf
	N13_1-s2.0-S009457651731562X-main.pdf
	N14_19810013548.pdf
	N3_S1063780X23600433.pdf
	N4_Probe Diagnostics of Plasma Parameters in a Large-Volume Glow Discharge ...
	N5_IJPAP4810723-730.pdf
	N6_3_Basu Ghimre_KUSET_August3_2014_edited.pdf.crdownload

	Name ▼	Version ▼
	20250407_VesselPumpDownCalculation.pdf	1.0
	6.Anewmethodfordeterminingwateradsorptionphenomenaonmetalsurfaceinava...	1.0
	A_new_model_for_vacuum_quality_and_lifetime_predic.pdf	1.0
	Cern_School_2006_Thermal_outgassing.pdf	1.0
	CERN_Water_outgassing_and_adsorption_isotherms_CScarcia (1).pdf	1.0
☐	CERN-Basic-Vacuum-2012-lecture.pdf ...	1.0
	Comparison-Of-Various-Adsorption-Isotherm-Models-For-Allium-Cepa-As-Corr...	1.0
	NIFS-389.pdf	1.0
	Outgassing_rate_paper_in_print.pdf	1.0
	p111.pdf	1.0
	Presentation1.pptx	1.0
	Rozanov_2016_J._Phys._Conf._Ser._729_012001.pdf	1.0
	SorptionIsothermSS.jpg	1.0
	SorptionIsothermSS.pdf	1.0
	SorptionIsothermSS.xlsx	1.0
	SorptionIsothermWaterSS.pdf	1.0
	TemkinIsotherm.pdf	1.0
	Thermal_outgassing_rates_of_low-carbon_steels.pdf	1.0
	VacCalculations.xmcd	1.0
	Water_outgassing_and_adsorption_isotherms_CScarcia.pdf	1.0

Setup design considerations

- Diameter-to-length ratio
- Vacuum levels
- Plasma generation
- Costs



Gas	Max pressure [mbar]
H ₂	6.0×10^{-11}
CH ₄	2.2×10^{-12}
H ₂ O	2.6×10^{-13}
CO	2.9×10^{-12}
CO ₂	1.3×10^{-12}

Tab. 8; Maximum ultimate partial pressures in the ET beam pipe after a 7-day bakeout at 150°C, following the layout presented in section 6.3.3. The ultimate pressures reported should be regarded as upper limits.

Vacuum
chamber

Plasma

Gas
control

RGA

Safety

Pumps

Pressure
sensors


Bake-out

Plasma
source


Plasma
head

Recondition
of wall

Control
system




Concept P&ID



Preferably the test-tube is so leak tight (i.c.w. HTT), that final total pressure is determined by water outgassing/H2 (and not by valve leaks etc).

- Tube**
- DN400CF: $d=0.40m$, $L=3d=1.20m$, $3L=3.60m$
 - DN450CF: $d=0.45m$, $L=1.35m$, $3L=4.05m$
 - Material 304L or 441 with HTT

When tube is to be isolated, the line pressure must be reduced to $<<1atm$ to limit valve leakage (depending on valve). Hence monitor line pressure?



Copilot ⓘ

Here's what the data shows about vacuum equipment and hardware prices compared to general inflation:

Conclusion:


Yes, vacuum equipment and related hardware prices have generally risen **faster than normal inflation**, especially in industrial and specialized segments. Household vacuum cleaners also show strong growth, but that's more due to **demand and product innovation** rather than pure inflation.

Copilot ⓘ

Here's what the data shows for **industrial and research-grade vacuum equipment** compared to general inflation:

Bottom Line:

Yes, **industrial and research vacuum equipment prices** have increased significantly faster than general inflation, mainly due to **technological complexity**, high demand in advanced industries, and supply chain constraints.




Plasma


Reduced test tube configuration to drastically cut back on HW costs (02-04-2025)

- Introduce zero length viewports & electrode feedthroughs
- Reduce tube diameter 400mm→300mm
- One electrode section (extent plasma tested by varying the tube length)
- Inner diameter $d=0.3\text{m}$, section length ($L=3d=0.9\text{m}$) $2L=6d=1.8\text{m}$, $4L=3.6\text{m}$
- Tube sections separately bakeable
- With preferred option we can realize tube length $2L$ and $4L$ with symmetric plasma (thus test extent plasma)

Options



Preferred option





Tube sections/components

EF1	End Flange 1	(TG	Gas flange)
TS1	Tube section 1	(TL	Long tube)
ES	Electrode section	(TE	Electrode section)
TS2	Tube section 2	(TS	Short tube)
PS	Pump section	(TP	Pump tube)
EF2	End Flange 2	(TV	Viewport flange)



Vacuum chamber

- Vacuum fired AISI 304, cold rolled 2B finish
- Total length 3,6 meters (excluding frame)
- 3 configurations possible
 - Need to validate efficiency of plasma at varies distances from plasma source



Plasma


- Long list of 10 plasma “types”
- Selected
 - RF 13,56 Mhz
 - DC Plasma
 - Or combined
- Shape of plasma antenna will ensure it will stay out of the beam path




Experimental plan

- Total project has two experimental phases
 - “fundamental”
 - “towards Einstein Telescope”
- During the fundamental phase we look at parameters like
 - Pressure
 - Plasma source
 - Plasma settings per source
 - Process gas? (default is N2)
- Efficiency of a setting is compared to 1 week bake-out @150°C
- During the “towards Einstein Telescope” phase we start limiting the parameter scope and
 - Increase measurement accuracy

“no limits”



Time-line



Outlook and conclusion

- Hardware is currently arriving (wk43 vacuum vessel)
- Installation is ongoing
- Validation of total setup to start in Oktober 2025
- Experimental risk
 - Cleaning efficiency of surfaces far away from plasma source
- “High risk, high gain” project
 - Fits well with the “yet to be invented technology” statement that is commonly used within the Einstein Telescope community
- A lot of experimental work ahead of us

Thank you for your attention

Acknowledgement

Part of this work is funded by the Dutch R&D
technology domain Einstein Telescope initiative



TNO innovation
for life



TNO innovation
for life